



US007337763B2

(12) **United States Patent**  
**Reitz et al.**

(10) **Patent No.:** **US 7,337,763 B2**  
(45) **Date of Patent:** **\*Mar. 4, 2008**

(54) **ENGINE VALVE ACTUATION FOR COMBUSTION ENHANCEMENT**

(75) Inventors: **Rolf Deneys Reitz**, Madison, WI (US);  
**Christopher J. Rutland**, Madison, WI (US);  
**Rahul Jhavar**, Madison, WI (US)

(73) Assignee: **Wisconsin Alumni Research Foundation**, Madison, WI (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/543,067**

(22) PCT Filed: **Jan. 16, 2004**

(86) PCT No.: **PCT/US2004/001292**

§ 371 (c)(1),  
(2), (4) Date: **May 15, 2006**

(87) PCT Pub. No.: **WO2005/068809**

PCT Pub. Date: **Jul. 28, 2005**

(65) **Prior Publication Data**

US 2006/0201481 A1 Sep. 14, 2006

(51) **Int. Cl.**  
**F02M 31/00** (2006.01)

(52) **U.S. Cl.** ..... **123/306**; 123/90.15; 123/568.14;  
123/316

(58) **Field of Classification Search** ..... 123/316,  
123/321, 322, 568.14, 90.15-90.18, 306  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,714,932 A 2/1973 Meacham et al.  
4,777,915 A 10/1988 Bonvallet  
4,829,947 A 5/1989 Lequesne

(Continued)

FOREIGN PATENT DOCUMENTS

DE 199 05 636 A1 3/2000

(Continued)

OTHER PUBLICATIONS

Kimura, S., Aoki, O., Kitahara, Y., and Aiyoshizawa, E., "Ultra-clean combustion technology combining a low-temperature and premixed combustion concept for meeting future emissions standards," SAE Paper 2001-01-200, 2001.

(Continued)


*Primary Examiner*—Erick Solis

(74) *Attorney, Agent, or Firm*—Craig A. Fieschko, Esq.;  
DeWitt Ross & Stevens S.C.

(57) **ABSTRACT**

A combustion chamber valve, such as an intake valve or an exhaust valve, is briefly opened during the compression and/or power strokes of a 4-strokes combustion cycle in an internal combustion engine (in particular, a diesel or CI engine). The brief opening may (1) enhance mixing within the combustion chamber, allowing more complete oxidation of particulates to decrease engine emissions; and/or may (2) delay ignition until a more desirable time, potentially allowing a means of timing ignition in otherwise difficult-to-control conditions, e.g., in HCCI (Homogeneous Charge Compression Ignition) conditions.

**19 Claims, 1 Drawing Sheet**



# US 7,337,763 B2

Page 2

## U.S. PATENT DOCUMENTS

4,974,566 A 12/1990 LoRusso et al.  
5,201,907 A 4/1993 Hitomi et al.  
5,224,460 A 7/1993 Havstad et al.  
5,228,422 A 7/1993 Wakeman  
5,353,763 A 10/1994 Schatz  
5,515,818 A 5/1996 Born  
5,832,880 A 11/1998 Dickey  
5,862,790 A 1/1999 Dai et al.  
6,012,424 A 1/2000 Meistrick  
6,082,328 A 7/2000 Meistrick et al.  
6,213,086 B1 4/2001 Chmela et al.  
6,230,683 B1 5/2001 zur Loye et al.  
6,286,482 B1 9/2001 Flynn et al.  
6,315,265 B1 11/2001 Adler et al.  
6,397,813 B1 6/2002 Han et al.  
6,405,706 B1\* 6/2002 Hammoud et al. .... 123/316  
6,439,210 B1 8/2002 Faletti et al.  
6,439,211 B1 8/2002 Juretzka et al.

6,460,337 B1 10/2002 Olofsson  
6,571,765 B2 6/2003 Kuboshima et al.  
6,736,106 B2 5/2004 Reitz et al.  
2002/0117131 A1 8/2002 Ladow  
2005/0235950 A1\* 10/2005 Weber et al. .... 123/299

## FOREIGN PATENT DOCUMENTS

DE 100 02 483 A1 7/2001  
EP 0473258 A2 3/1992  
EP 0 961 018 A 12/1999  
EP 1136682 A 9/2001  
FR 2476741 8/1981  
WO WO 01/46573 A 6/2001

## OTHER PUBLICATIONS

European Patent Office examination report of Oct. 16, 2006 for corresponding European application.

\* cited by examiner





FIG. 2



1

## ENGINE VALVE ACTUATION FOR COMBUSTION ENHANCEMENT

### STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

This invention was made with United States government support awarded by the following agencies:

U.S. Department of Energy Grant No(s): DE-FC04-02AL67612 The United States has certain rights in this invention.

### FIELD OF THE INVENTION

This disclosure concerns an invention relating generally to combustion methodologies for internal combustion engines, and more specifically to combustion methodologies resulting in decreased pollutant emissions.

### BACKGROUND OF THE INVENTION

For better understanding of the invention described in this document, it is initially useful to review basic principles of internal combustion engine structure and operation. FIG. 1 depicts a cylinder in a simple idealized internal combustion engine **100**, including a combustion chamber **102** defined between a piston **104** and a cylinder head **106**. The cylinder head **106** includes a fuel injector **108** and a pair of combustion chamber valves, an intake valve **110** for intake of air from an intake manifold **112**, and an exhaust valve **114** for exhaust of combustion products to an exhaust manifold **116** and exhaust system. As is well known, the engine **100** operates by engaging in a combustion cycle, wherein fuel is burned in the combustion chamber **102** to expand the gases (primarily air) therein and drive the piston **104**. The piston **104** in turn drives a crank **118** associated with the piston **104**, with the crank **118** in turn driving the crankshaft (not shown) which provides power output for a vehicle drive train or to other structures for transmitting mechanical power. The classical four-stroke combustion cycle for both SI (spark ignition or gasoline) engines and CI (compression ignition or diesel) engines involves the following steps:

(1) An intake stroke, wherein the intake valve **110** is opened while piston **104** retreats from cylinder head **106** to draw air into the combustion chamber **102** from the intake manifold **112**.

(2) A compression stroke, wherein the piston **104** approaches cylinder head **106** with the combustion chamber valves **110** and **114** closed (at least during the latter portion of the stroke).

(3) A power or expansion stroke, wherein fuel injected into the combustion chamber **102** is ignited and the expanding gases within the combustion chamber **102** push the piston **104** outwardly (as during the intake stroke). Again, the combustion chamber valves **110** and **114** usually remain closed (at least during the early portion of the stroke).

(4) An exhaust stroke, wherein the combustion products within the combustion chamber **102** are expelled to the exhaust manifold **116** by advancing the piston **104** towards the cylinder head **106** with the exhaust valve **114** open.

Each stroke occurs over 180 degrees of crankshaft rotation, with the entire cycle thereby occurring over 720 degrees (two full crankshaft revolutions). The combustion chamber valves **110** and **114** are usually opened and closed at the desired times by valve actuators such as cams or other structures, which are in turn driven by the crankshaft (not shown). Since such arrangements couple the timing and

2

extent of valve opening and closing to the positioning of the crankshaft, and since it may be desirable to have a greater degree of control over valve actuation to achieve desired combustion chamber conditions, there has been a recent trend towards the use of variable valve timing technologies. These technologies wholly or partially decouple the timing and/or extent of valve actuation from the crankshaft position, and allow the valves **110** and **114** to be opened and/or closed when desired (and may also allow the degree of opening to be varied as desired). Examples of variable valve actuation (VVA) schemes may be found, for example, in U.S. Pat. Nos. 4,777,915; 4,829,947; and 5,515,818.

The foregoing combustion cycle steps/strokes differ between classical SI and CI engines in that SI engines tend to inject fuel during the intake stroke, whereas CI engines tend to inject fuel late in the compression stroke or early in the power stroke, close to "top dead center" (TDC), the piston **104**'s point of closest approach to the cylinder head **106**. Additionally, in SI engines, ignition of the fuel/air mixture occurs by introduction of a spark (with no spark plug being illustrated in FIG. 1). In contrast, classical CI engines rely on the compression stroke to increase the heat and pressure in the combustion chamber **102** to such a degree that ignition results. There are also various types of "hybrid" engines which operate using a combination of SI and CI principles, or example, engines which run primarily on CI principles but which use a spark or "glow plug" to assist with ignition. (Also note that the engine of FIG. 1 is described as a "simple idealized" one since real-world engines may have a wide variety of combustion chamber configurations other than those shown at **102** in FIG. 1, and may have varying numbers, locations, and configurations of combustion chamber valves **110** and **114** and/or injectors **108**.)

In the field of engine development and manufacture, two concerns of critical importance are engine efficiency (e.g., power output per fuel consumption) and engine emissions. Diesel engines tend to operate more efficiently than SI engines, but they unfortunately also tend to have much greater pollutant emissions than SI engines. Common pollutants arising from the use of internal combustion engines are nitrogen oxides (commonly denoted NO<sub>x</sub>) and particulates (also known simply as "soot"). NO<sub>x</sub> is generally associated with high-temperature engine conditions, and may be reduced by use of measures such as exhaust gas recirculation (EGR), wherein the engine intake air is diluted with relatively inert exhaust gas (generally after cooling the exhaust gas). This reduces the oxygen in the combustion chamber and obtains a reduction in maximum combustion temperature, thereby deterring NO<sub>x</sub> formation. Particulates (soot) include a variety of matter such as elemental carbon, heavy hydrocarbons, hydrated sulfuric acid, and other large molecules, and are generally associated with incomplete combustion. Particulates can be reduced by increasing combustion and/or exhaust temperatures, or by providing more oxygen to promote oxidation of the soot particles. Unfortunately, measures which reduce NO<sub>x</sub> tend to increase particulate emissions, and measures which reduce particulates tend to increase NO<sub>x</sub> emissions, resulting in what is often termed the "soot-NO<sub>x</sub> tradeoff".

At the time of this writing, the diesel engine industry is facing stringent emissions legislation in the United States, and is struggling to find methods to meet government-imposed NO<sub>x</sub> and soot targets for the years 2002-2004 and even more strict standards to be phased in starting in 2007. One measure under consideration is use of exhaust after-treatment (e.g., particulate traps) for soot emissions control

in both heavy-duty truck and automotive diesel engines. However, in order to meet mandated durability standards (e.g., 50,000 to 100,000 miles), the soot trap must be periodically regenerated (the trapped soot must be periodically re-burned). This requires considerable expense and complexity, since typically additional fuel must be mixed and ignited in the exhaust stream in order to oxidize the accumulated particulate deposits.

Apart from studies directed to after-treatment, there has also been intense interest in the more fundamental issue of how to reduce  $\text{NO}_x$  and particulates generation from the combustion process and thereby obtain cleaner "engine out" emissions (i.e., emissions directly exiting the engine, prior to exhaust after-treatment or similar measures). Studies in this area relate to shaping combustion chambers, timing the fuel injection, tailoring the injection rate during injection so as to meet desired emissions standards, or modifying the mode of injection (e.g. modifying the injection spray pattern). One field of study relates to premixing methodologies, wherein the object is to attain more complete mixing of fuel and air in order to simultaneously reduce soot and  $\text{NO}_x$  emissions. In diesel engines, the object of premixing methodologies is to move away from the diffusion burning mechanism which drives diesel combustion, and instead attempt to attain premixed burning. In diffusion burning, the oxidant (fuel) is provided to the oxidizer (air) with mixing and combustion occurring simultaneously. The fuel droplets within an injected spray plume have an outer reaction zone surrounding a fuel core which diminishes in size as it is consumed, and high soot production occurs at the high-temperature, fuel-rich spray core. In contrast, premixed burning mixes fuel and air prior to burning, and the more thorough mixing results in less soot production. Premixing may be performed by a number of different measures, such as by use of fumigation (injection of fuel into the intake airstream prior to its entry into the engine), and/or direct injection of a fuel charge relatively far before top dead center (TDC) so that motion of the piston **104**, and convection within the cylinder, result in greater mixing.

One promising diesel premixing technology is HCCI (Homogeneous Charge Compression Ignition), which has the objective of causing initial ignition of a lean, highly premixed air-fuel mixture at or near top dead center (TDC). An extensive discussion on HCCI and similar premixing techniques is provided in U.S. Pat. No. 6,230,683 to zur Loye et al., and U.S. Pat. No. 5,832,880 to Dickey and U.S. Pat. No. 6,213,086 to Chmela et al. also contain useful background information. The charge is said to be "homogeneous" in HCCI because it is (at least theoretically) highly and evenly mixed with the air in the cylinder. Ignition is then initiated by autoignition, i.e., thermodynamic ignition via compression heating. The objective of HCCI is to use autoignition of the lean and homogeneous mix to provide a uniform and relatively slow non-diffusion (or minimized diffusion) burn, resulting in significantly lower combustion chamber temperatures and diminished  $\text{NO}_x$  production (which thrives at high temperature), as well as lower soot production owing to enhanced mixing. In contrast, a richer mixture (such as that necessary for flame propagation from the spark in an SI engine) will burn more quickly at greater temperature, and therefore may result in greater  $\text{NO}_x$  production.

Another promising premixing technology is the Modulated Kinetics (MK) technique, which might be regarded as being a species of HCCI. MK combustion is primarily characterized by three features: (1) a leaner-than-usual fuel/air mixture is used; (2) injection is made at or near top dead

center (often after TDC); and (3) the ignition delay exceeds the injection duration (so that the fuel/air mixture is at least partially premixed prior to combustion). In essence, MK combustion involves use of relatively late injection(s) in the "general" HCCI combustion method described above, and concentrates on using the ignition delay for premixing. For further discussion on MK combustion, see, e.g., Kimura et al., "Ultra-clean combustion technology combining a low-temperature and premixed combustion concept for meeting future emissions standards," SAE paper 2001-01-200, 2001.

As the foregoing references note, while HCCI-type premixing processes might be beneficially implemented in CI engines to achieve their high efficiency without their customarily high emissions, HCCI is also hard to accomplish owing to the difficulties in igniting the lean mix and/or controlling the start of ignition. Combustion in an SI engine is readily initiated by the spark, with premixed burning occurring afterward; similarly, combustion in a conventional CI engine is initiated by fuel injection near top dead center (at or slightly after the end of the compression stroke) when thermodynamic conditions for autoignition are favorable, with diffusion burning occurring afterward. However, HCCI does not utilize a spark, nor is it desirable for HCCI to use the rich mixture needed for effective use of a spark. It is also difficult for HCCI to achieve a homogeneous charge or premixed burning if injection near top dead center is used, since there is less time for mixing to occur before ignition. Thus, a key area of study in the HCCI field is how to efficiently initiate ignition, and more critically, how to effect ignition at the desired time. While these issues are somewhat straightforward where CI engines operate under a relatively rigid set of operating conditions (as with diesel generators, which tend to operate at relatively constant speeds and loads), these issues become exceedingly complex where CI engines must operate at varying speeds and loads (as in automotive/vehicular operations). These ignition and timing problems are the primary reason why HCCI methodologies have not attained widespread use outside of generators and other constant speed/load applications.

In view of the foregoing discussion, there is a significant need for methods and apparatus which assist in obtaining premixed burning, particularly premixed burning which achieves or approximates HCCI burning, so as to allow exploitation of the high efficiency of CI engines without the detriment of their high pollutant emissions.

Other prior patents which are usefully considered include U.S. Pat. Nos. 3,714,932; 4,974,566; 5,201,907; 5,224,460; 5,228,422; 5,353,763; 6,286,482; 6,397,813; 6,439,210; 6,439,211; 6,460,337; and 6,571,765; and particularly U.S. Pat. No. 5,862,790 to Dai et al. and U.S. Pat. No. 6,405,706 to Hammoud et al.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a simplified cross-sectional view of an exemplary internal combustion engine cylinder.

FIG. 2 is a diagram depicting exemplary time periods during which the intake valve may be opened over the course of an engine cycle (with the intake valve being only briefly opened at some time during the second period).

#### DETAILED DESCRIPTION OF PREFERRED VERSIONS OF THE INVENTION

The invention, which is defined by the claims set forth at the end of this document, is directed to methods which at least partially alleviate the aforementioned problems. To

allow a reader to better compare the invention to the preexisting technology described above, preferred features of the invention will now be more specifically described with reference to FIG. 1. Thus, it should be understood that while FIG. 1 bears the label “prior art” to denote that the exemplary structure shown therein is well known, the following description describes how the invention might be implemented in previously-known engines of the type shown in FIG. 1 or of other types (though it should also be understood that the invention might be implemented in other types of engines which are yet to be developed).

A particularly preferred version of the invention involves briefly opening at least one of the combustion chamber valves **110** and **114** for at least one discrete period sometime during the compression and/or power strokes, resulting in one or more of the following benefits:

(1) Greater mixing may be obtained within the combustion chamber **102**. If one of the combustion chamber valves **110** and **114** is opened for a brief period, the gases within the combustion chamber **102** will rapidly exit from the opened valve into its associated manifold **112** or **116** during this period. The escaping gases may generate mixing flows within the combustion chamber **102**, which may enhance burning of particulates and thereby result in lower emissions.

(2) The conditions in combustion chamber **102** can be altered to effect a change in the time ignition is initiated, thereby allowing the ignition timing to be varied as desired to achieve HCCI. Since ignition timing is largely dependent on the pressure (and temperature) of the gases within the combustion chamber **102**, releasing the combustion chamber **102** gases by briefly opening one or more of the combustion chamber valves **110** and/or **114** will introduce an ignition delay depending on the resulting drop in pressure (and temperature). Thus, by opening one or more combustion valves **110** and/or **114** (and opening them simultaneously or sequentially, where multiple valves are opened), one can tailor combustion chamber pressures (and to some degree temperatures) so that peak values can be precisely timed, allowing control over ignition timing.

Since the pressure generated within the combustion chamber **102** is used to generate the power output from the engine **100**, it might be regarded as contrary to the purposes of the engine **100** to open one or more of the combustion chamber valve(s) **110** and/or **114** for a discrete period sometime during the compression and/or power strokes: the release of pressure from the combustion chamber **102** results in a power loss. However, the power loss may be acceptable if emissions reduction and other objectives are met. The pressure loss within the combustion chamber **102** will depend on the length of the period during which the combustion chamber valve(s) **110** and/or **114** is/are opened, and the degree to which they are opened. It is believed that the benefits of the invention would best be achieved if the period and extent of valve opening be limited such that no more than 20% of the mass of the combustion chamber **102** contents (as measured after fuel injection) be released during an discrete openings of the valves **110** and **114** during the compression and/or power strokes, since computerized engine simulations appear to indicate that more substantial power losses occur if more than approximately 15% of the combustion chamber **102** mass is released.

It follows from the foregoing that it will usually be desirable to implement the invention in such a manner that any mixing and/or ignition timing objectives are met while releasing as little of the combustion chamber mass (and thus pressure) as possible. Thus, it is expected that when the

invention is implemented in most diesel engines by a single opening of a single one of the combustion chamber valves **110** and **114** to its fully open position (or nearly so), it will usually be desirable to open the valve for no more than 5 degrees of crankshaft revolution, since computerized engine simulations indicate that more substantial power losses occur above approximately 7 degrees. More preferably, the period will not exceed approximately 5 degrees. Where the invention is implemented by opening more than one combustion chamber valve (e.g., by opening both an intake valve **110** and an exhaust valve **114**, or by opening more than one intake and/or exhaust valve **114** where multiple intake valves **110** and/or exhaust valves **114** are present), it is expected that the foregoing parameters would apply to the cumulative openings of the valves **110** and **114**. The same principle applies where a combustion chamber valve is opened more than once during compression and/or power strokes.

The timing of the valve opening may also vary depending on which of the two aforementioned benefits is to be achieved, and the degree to which it is to be achieved. It is expected that the objective of greater mixing is best accomplished if one or more of the combustion chamber valves **110** and **114** is opened during the first half of the power stroke, most preferably within about 50 degrees after TDC (i.e., approximately the first quarter of the power stroke). At this time, ignition has usually started and combustion is underway.

In contrast, to achieve the objective of ignition timing, it is expected that any openings of the valves **110** and **114** are usually best implemented starting in the latter half of the compression stroke, most preferably at 50 degrees before TDC or thereafter. Openings of the valves **110** and **114** could occur earlier, but since ignition delay occurs with each valve opening owing to pressure release from the combustion chamber **102**, and ignition is usually desired late in the compression stroke or early in the expansion stroke, openings of the valves **110** and **114** during the latter half of the compression stroke (particularly at about 30 degrees before TDC and thereafter) should afford more precise control of ignition timing.

The foregoing discussion suggests that where ordinary engine speed/load conditions are presumed, the mixing objective is generally better achieved with openings of the valves **110** and **114** after TDC, whereas the ignition timing objective is generally better achieved with openings of the valves **110** and **114** before TDC. However, openings of the valves **110** and **114** before TDC will have an impact on mixing as well. Similarly, openings of the valves **110** and **114** after TDC may also have an impact on ignition timing provided ignition has not already begun. To illustrate, some combustion schemes—such as the Modified Kinetics (MK) combustion methodology, where ignition is often desired after the power stroke has begun—may benefit from valve openings after TDC to control ignition timing.

As noted above, the invention may be accomplished by opening more than one of the intake and/or exhaust valves **110** and **114**, and/or by opening one or more of these valves more than once during a combustion cycle. It is expected that it will generally be most beneficial to open one or more intake valves **110**, since any unburned fuel and/or particulates ejected from the combustion chamber **102** will then be retained in the intake manifold **112** for later readmission into the combustion chamber **102** during the next intake stroke. The unburned fuel and particulates (if any) ejected from the intake valve(s) **110** during one combustion cycle will therefore be taken up for consumption in the following cycle. In

contrast, if the invention is implemented by alternatively or additionally opening one or more exhaust valves **114**, any unburned fuel and/or particulates escaping the combustion chamber **102** will exit to the exhaust manifold **116** to exit as pollutant emissions (unless some form of after-treatment is applied to the exhaust gases). Owing to these emissions, it is expected that implementation of the invention by opening one or more exhaust valves **114** will generally be undesirable, unless any resulting emissions are outweighed by any corresponding mixing and/or ignition timing benefits.

In some instances, opening of exhaust valves **114** warrants serious consideration despite any emissions drawbacks. To illustrate, since exhaust valves **114** are often spaced at opposite ends of the combustion chamber **102** from any intake valves **110**, it may in some cases be beneficial to first open an exhaust valve **114** and then an intake valve **110**, or conversely first open an intake valve **110** followed by opening of an exhaust valve **114**, to better achieve thorough mixing throughout the entirety of the combustion chamber **102**. By opening the valves **110** and **114** at different times, a sort of back-and-forth “sloshing” effect is achieved in the contents of the combustion chamber **102**, resulting in thorough mixing. However, the same effect might be accomplished by only opening intake valves **110** if multiple spaced intake valves **110** are present.

Since most standard valve actuation schemes couple valve actuation to crankshaft motion, and it would often be difficult and expensive to modify any cams or other intervening structure to effectively actuate the valves to implement the invention, it is expected that the invention would make beneficial use of variable valve actuation (VVA) technologies. Since variable valve actuators (VVAs) allow precise control of valve opening and closing times, and/or to the degree of valve opening/closing, they allow a readily available means for implementing the invention.

At various points in the foregoing discussion, preferred operating parameters were noted for the invention, with such parameters being determined in view of computerized engine simulations. These simulations were performed using WAVE simulation software (Ricardo PLC, Shoreham-by-Sea, West Sussex, England) with a Caterpillar 3401E SCOTE engine (Caterpillar Inc., Peoria, Ill., USA) running at 821 rpm, 25% load, with 61.2 mg of fuel being injected per cycle starting at 20 degrees before TDC. It should be understood that different preferred operating parameters might be derived if engines having different configurations and/or operating conditions are tested.

Note that various preferred versions of the invention are shown and described above to illustrate different possible options for the invention and the varying ways in which these options may be combined. Apart from combining the different options of the foregoing versions of the invention in varying ways, other modifications are also considered to be within the scope of the invention. Following is an exemplary list of such modifications.

First, any variable valve actuators (VVAs) used to implement the invention may make use of regeneration methodologies, i.e., recovery of energy which would otherwise be lost by the engine or by associated components, to better decrease energy demands from valve actuation. Exemplary regeneration methodologies may be seen in U.S. Pat. No. 6,315,265 (recovery of energy captured from valve during

valve deceleration), as well as in U.S. Pat. Nos. 6,082,328 and 6,012,424 (recovery of energy from vehicle braking systems).

Second, the invention might be implemented by opening a combustion chamber valve other than an intake valve (or valves) and/or an exhaust valve (or valves). For example, a combustion chamber might be separated from an adjacent supplemental chamber (provided outside the cylinder) by a supplemental combustion chamber valve which serves neither intake nor exhaust purposes. The combustion chamber contents might be “vented” into this supplemental chamber at appropriate times to serve the mixing and/or ignition timing functions of the invention.

Third, while the invention is believed to have most beneficial application to CI engines, it might be utilized in SI engines as well (particularly in SI engines implementing HCCI-type or similar combustion schemes). In this case, the primary benefit of the invention would likely result from the enhanced mixing that the invention can provide, rather than from ignition timing modification (which is more readily controlled in an ST engine via spark timing).

The invention is not intended to be limited to the preferred versions of the invention described above, but rather is intended to be limited only by the claims set out below. Thus, the invention encompasses all different versions that fall literally or equivalently within the scope of these claims.

What is claimed is:

1. A method for modifying combustion in a combustion chamber of a 4-stroke internal combustion engine running under standard warm (non-starting) engine temperatures, the method comprising the step of briefly opening a combustion chamber intake valve sometime during a period spanning:
  - a. the latter half of the compression stroke, and
  - b. the first half of the power stroke,
 such opening being subsequent to the closing of the same intake valve during the intake stroke, and solely allowing the escape of combustion chamber gases.
2. The method of claim 1 wherein the briefly opening of the combustion chamber intake valve effects an escape of no greater than approximately 15% of the mass of the combustion chamber contents.
3. The method of claim 1 wherein the combustion chamber intake valve is briefly opened two or more times during the period.
4. The method of claim 1 wherein the combustion chamber intake valve is briefly opened during the period of crankshaft rotation between:
  - a. 50 degrees before top dead center, and
  - b. 50 degrees after top dead center.
5. The method of claim 1 where in the combustion chamber intake valve is briefly opened during the period of crankshaft rotation between:
  - a. 30 degrees before top dead center, and
  - b. 30 degrees after top dead center.
6. The method of claim 1 where in the combustion chamber intake valve is briefly opened for no greater than approximately 7 degrees of crankshaft rotation.
7. The method of claim 1 wherein the combustion chamber intake valve is briefly opened for no greater than approximately 5 degrees of crankshaft rotation.
8. The method of claim 1 wherein the combustion chamber intake valve is briefly opened for no greater than approximately 3 degrees of crankshaft rotation.

## 9

9. The method of claim 1 wherein the combustion chamber intake valve is briefly opened at or substantially near the time of ignition.

10. The method of claim 1 wherein multiple combustion chamber intake valves are briefly opened during the period.

11. The method of claim 10 wherein at least some of the multiple combustion chamber intake valves are briefly opened during the period starting at different times.

12. A method for modifying combustion in a combustion chamber of a 4-stroke internal combustion engine running under standard warm (non-starting) engine temperatures, the method comprising the step of briefly opening a combustion chamber intake valve during a period extending over at least one of the compression stroke and the power stroke, with such brief opening:

- a. being subsequent to the closing of the same intake valve during the intake stroke, and
- b. being subsequent to the first half of the compression stroke, and
- c. effecting an escape of no more than approximately 15% of the mass of the combustion chamber contents.

13. The method of claim 12 wherein the combustion chamber intake valve is briefly opened two or more times during the period.

## 10

14. The method of claim 12 wherein the combustion chamber intake valve is briefly opened during the period of crankshaft rotation between:

- a. 50 degrees before top dead center, and
- b. 50 degrees after top dead center.

15. The method of claim 12 wherein the combustion chamber intake valve is briefly opened during the period of crankshaft rotation between:

- a. 30 degrees before top dead center, and
- b. 30 degrees after top dead center.

16. The method of claim 12 wherein the combustion chamber intake valve is briefly opened for no greater than approximately 7 degrees of crankshaft rotation.

17. The method of claim 12 wherein the combustion chamber intake valve is briefly opened at or substantially near the time of ignition.

18. The method of claim 12 wherein multiple combustion chamber intake valves are briefly opened during the period.

19. The method of claim 18 wherein at least some of the multiple combustion chamber intake valves are briefly opened during the period starting at different times.

\* \* \* \* \*