



Ultra Low Radiation Dose Computed Tomography Scanner for X-ray Mammography

[View U.S. Patent No. 8,005,184 in PDF format.](#)

WARF: P05204US

Inventors: Guang-Hong Chen

The Wisconsin Alumni Research Foundation (WARF) is seeking commercial partners interested in developing a line scan X-ray cone beam computed tomography (CT) scanner system and method with an ultra low radiation dose to provide high in-plane spatial resolution and excellent low contrast resolution.

Overview

Breast cancer is the most common cancer among women today with all women having approximately an 11 to 12 percent chance of developing this cancer and a 30 to 40 percent chance of death after development. X-ray mammography is the best detection method, which reduces mortality by 30 to 50 percent. However, 30 percent of breast cancers cannot be detected by this method due to large amounts of noise, low resolution, dense breast tissue, normal tissue mimicking tumors and other reasons. The median detectable breast cancer tumor size is 11mm, but the spread of the tumor to other areas, or metastasis, can occur 16 months before the tumor reaches a detectable size. If the detectable size is reduced to 3mm the tumor can be detected 18 months earlier, before metastasis.

The two preferred X-ray mammography techniques are tomosynthesis imaging and dedicated cone beam computed tomography (CT) breast imaging. Tomosynthesis has superior 2-D, or "in-plane," imaging resolution, but very low resolution in the third dimension. Cone beam CT has very good isotropic 3-D spatial resolution for superior contrast resolution to distinguish cancerous tissue from normal tissue, but low 2-D in-plane resolution. To minimize radiation dose to the patient it would be preferable to combine the benefits of both imaging techniques.

The Invention

A UW-Madison researcher has developed a line scan X-ray cone beam CT scanner system and method with an ultra low radiation dose to provide high in-plane spatial resolution and excellent low contrast resolution. The system is made up of an x-ray cone beam source and a 2-D X-ray detector array. Both move linearly on opposing sides of the breast in opposite directions to capture data from various angles. They do not move in a circular pattern around the breast.

An image is reconstructed with the data from a limited amount of angles, which results in a significantly lower X-ray dose to the patient. The cone beam data is converted into a parallel beam projection data set to create an image using a novel image reconstruction method. This method determines the image quality by using a determined metric to measure it against with the image quality continually increased until a preset quality is met. The limited number of angles required for this method leads to an approximate 20-fold reduction in radiation dose.

Applications

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. See our [privacy policy](#).

OK



WARF
Wisconsin Alumni Research Foundation

| info@warf.org | 608.960.9850

Key Benefits

- Significantly lower radiation dose (around 20-fold lower) to patient
- Able to detect smaller clusters of cancerous tissue with higher resolution images
- Excellent low contrast resolution to distinguish cancerous tissue from normal tissue

Additional Information

For More Information About the Inventors

- [Guang-Hong Chen](#)

Tech Fields

- [Medical Imaging : CT](#)
- [Medical Imaging : X-ray](#)

For current licensing status, please contact Jeanine Burmania at jeanine@warf.org or 608-960-9846

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

OK



WARF
Wisconsin Alumni Research Foundation

| info@warf.org | 608.960.9850