



Recyclable Catalyst for Lower Cost Production of Fermentable Sugars and High Value Chemicals from Biomass

WiSys: T170034US02

Inventors: Malek Alkasrawi, Joynal Abedin

WiSys is currently seeking a strategic partner in the lignocellulose processing, aromatic chemical, and cellulosic biofuel industries that are interested in further developing and scaling up this novel fractionation process, ultimately providing a route to market for its commercialization.

Overview

Lignocellulose is plant biomass that is the most abundantly available raw material on Earth for producing end products such as biofuels and certain high value chemicals. Processes currently exist to separate this biomass into cellulose and lignin fractions, convert them to fermentable sugars and cyclic compound intermediates, and ultimately generate the desired end products. However, the cost is still greater than that of petroleum-based production. This is because complex, time-consuming and expensive pretreatment steps using acids and enzymes are required to make lignocellulosic biomass accessible for further processing.

The Invention

An assistant professor in chemical engineering at the University of Wisconsin-Stevens Point and former senior research scientist at the Montana State University Bio-Energy Center have developed a technology that reduces the processing cost and time to fractionate lignocellulose into fermentable sugars. The technology is centered on the use of a catalyst linked to a magnetic bead, which replaces the need for acids and enzymes in the pretreatment step of the production process. Because of its magnetic properties, the catalyst can easily be recovered from the reaction mixture and reused multiple times. It is also capable of functioning under cellulose loads as high as 50%, whereas loads for competing solid acid catalysts have been typically limited to less than 15%. The end result is a process that makes better use of carbon-neutral biomass by lowering production costs and increasing yield of desirable monomer sugars and high value chemical compounds such as vanillin, phenol, acetophenone.

Applications

- Production of high value chemicals – vanillin, phenol, acetophenone, phenolic based compounds;
- Cellulosic ethanol production.

Key Benefits

- Two revenue streams - high value chemicals and biofuels;
- Magnetic catalyst: works with both lignin and cellulosic wood; can be reused for multiple fractionations; reduces, or eliminates, the need for acids and enzymes in fractionation reactions; works with higher cellulose loads than other methods currently in use; high specificity for production of desirable monomer sugars;
- Produces high concentration of sugars;
- Process cost reduction makes lignocellulosic materials more competitive than petroleum-based materials;
- Promotes use of carbon-neutral biomass;
- Commercial use of agricultural waste.

Stage of Development

This magnetic catalyst technology has been produced and tested at laboratory scale. Operational parameters, including temperature, pressure and reaction solvent have been optimized. The catalyst has demonstrated success in simultaneously fractionating lignin and cellulose directly from softwood and other biomass materials. In addition, four rounds of enzyme recycling have shown no effects on conversion rate and yield of desired end products.

Additional Information

Tech Fields

- [Clean Technology : Biofuels & renewable fuels](#)
- [Materials & Chemicals : Biochemicals](#)

For current licensing status, please contact Jennifer Souter at jennifer@wisys.org or (608) 316-4131