



Metal-Coated Vertically Aligned Carbon Nanofibers

[View U.S. Patent No. 8,491,999 in PDF format.](#)

WARF: P06357US

Inventors: Robert Hamers, Kevin Metz

The Wisconsin Alumni Research Foundation (WARF) is seeking commercial partners interested in developing a method for decorating carbon nanostructures with uniform metal coatings to provide electrodes with high structural stability and surface area.

Overview

Although electrochemically active materials with high density and surface area have many potential uses in electrocatalysts, batteries, fuel cells and sensors, creating these materials can be challenging. Vertically aligned carbon nanofibers are a promising option. In addition to having similar electrochemical and mechanical properties as other nanoscale carbon materials, the physical dimensions of these nanofibers can be controlled to allow for large, accessible surface areas.

The Invention

UW-Madison researchers have developed a method for decorating carbon nanostructures with uniform metal coatings to provide electrodes with high structural stability and surface area. The process uses arrays of vertically aligned carbon nanofibers separated by interstices. The nanofibers are functionalized by covalently binding a layer of organic linker molecules to their surface. Electroless deposition is then used to deposit a continuous metal coating onto the functionalized surfaces. The resulting metal-coated nanofibers form highly stable and reproducible electrodes with high surface areas. These electrodes can be used in devices such as supercapacitors and fuel cells.

Applications

- High-density energy storage (i.e., supercapacitors and fuel cells)

Key Benefits

- Because of the shape and accessibility of the carbon nanofibers, the resulting structures are highly stable and reproducible, and have high surface areas.
- Electrodes have approximately 10 times greater capacitance than carbon nanofiber electrodes and approximately 100 times greater capacitance than typical planar surfaces.
- Because the nanofibers are organized into brush-like arrays, rather than randomly oriented into spaghetti-like mats, the analytes used for functionalizing or coating the nanofiber surfaces can easily access the nanofibers.
- Electroless deposition uniformly and continuously coats the entire length of the nanofiber, rather than just the top, as is seen with electrochemical deposition.
- In some embodiments, at least 75 percent of the weight of the metal-coated nanofibers comes from the metal.

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

- Many forms of vertically aligned carbon nanofiber arrays are used.
- Many types of metals, such as Ag, Au, Pd, Pt, Rh, Cu or Ni, are used to coat the nanofibers.

OK



WARF
Wisconsin Alumni Research Foundation

| info@warf.org | 608.960.9850

- Nanofibers can be grown on a variety of electrically conductive substrate surfaces, including silicon nitride, silicon oxide, silicon, molybdenum, stainless steel and titanium.

Additional Information

For More Information About the Inventors

- [Robert Hamers](#)

Tech Fields

- [Clean Technology : Energy storage, delivery & resource efficiencies](#)
- [Engineering : Micro & nanotechnologies](#)

For current licensing status, please contact Mark Staudt at mstaudt@warf.org or 608-960-9845

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

OK



WARF
Wisconsin Alumni Research Foundation

| info@warf.org | 608.960.9850