

Producing Methyl Vinyl Ketone from Levulinic Acid

View U.S. Patent No. 7,960,592 in PDF format.

WARF: P09350US01

Inventors: James Dumesic, Ryan West

The Wisconsin Alumni Research Foundation (WARF) is seeking commercial partners interested in developing a method to convert inexpensive biomass-derived carboxylic acids such as levulinic acid into methyl vinyl ketone, a valuable industrial compound.

Overview

Levulinic acid is a biomass-derived compound that can be obtained inexpensively in high yields from a variety of waste cellulosecontaining materials. It has been identified as a top biomass-derived chemical due to its ease of production for both five and six carbon sugars and its useful functional groups, a ketone and a carboxylic acid. There are several possible reactive pathways for levulinic acid to form other, more valuable reactive chemicals including methyl vinyl ketone. Methyl vinyl ketone is valuable for many industrial processes because it contains two useful functional groups, an olefin and a ketone. It also is used to produce polymers and other chemical production pathways.

Previously, research has focused on dehydrogenation and hydrogenation reactions of levulinic acid as methods to produce these intermediate chemicals. Unfortunately, these methods to produce methyl vinyl ketone require expensive starting materials, catalysts and reactive conditions. More recent work has been focused on producing chemicals from levulinic acid without the addition of hydrogen, which could decrease costs associated with catalysts and reactive conditions. An inexpensive, commercially viable method to produce methyl vinyl ketone from levulinic acid is needed.

The Invention

UW-Madison researchers have developed an efficient method to convert levulinic acid to methyl vinyl ketone. The method involves performing a reaction with an aqueous solution comprising levulinic acid over an acid catalyst, preferably a solid acid catalyst, at a temperature from 500 to about 900 Kelvin and without added molecular hydrogen. The reaction can be performed in either a batch or continuous reactor, although a continuous reactor is preferred. The reaction produces methyl vinyl ketone at higher yields from less expensive starting material compared to current methods.

Applications

- Conversion of levulinic acid to methyl vinyl ketone in a single reactor
- Coupling with the industrial production of levulinic acid through inexpensive routes, for example the Biofine process, to convert renewable lignocelluloses resources

Key Benefits

- Produces methyl vinyl ketone at yields greater than 90 percent
- We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete • Converts an inexpensive, renewable resource (levulinic acid) into useful intermediate methyl vinyl keyne in one step

Additional Information



Related Technologies

• For more information about producing liquid fuels from levulinic acid, see WARF reference number P09298US.

Publications

• Kunkes E.L., Simonetti D.A., West R.M., Serrano-Ruiz J.C., Gärtner C.A. and Dumesic J.A. 2008. Catalytic Conversion of Biomass to Monofunctional Hydrocarbons and Targeted Liquid-Fuel Classes. Science 322, 417-421.

Tech Fields

- <u>Clean Technology : Energy storage, delivery & resource efficiencies</u>
- Materials & Chemicals : Synthesis

For current licensing status, please contact Jennifer Gottwald at jennifer@warf.org or 608-960-9854

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. See our privacy policy

