



Smoother Waveguides for More Efficient Nonlinear Frequency Conversion

[View U.S. Patent No. 9,096,948 in PDF format.](#)

WARF: P120326US01

Inventors: Dan Botez, Thomas Kuech, Luke Mawst, Steven Ruder

The Wisconsin Alumni Research Foundation (WARF) is seeking commercial partners interested in developing methods for fabricating orientation-patterned semiconductor structures able to generate visible, mid- or near-infrared light with low optical losses.

Overview

For many applications – from remote sensing to laser displays – it is necessary to convert the frequency of light via nonlinear interaction in semiconductor materials. Waveguide devices accomplish this efficiently by receiving radiation from an input source, such as an optical fiber, and directing it along an axis. Upon exiting the other end, the frequency-converted output radiation is collected or redirected for different purposes.

Orientation-Patterned GaAs (OPGaAs) waveguide structures hold promise for efficient, mid-infrared nonlinear frequency conversion. However, thickness variations between the device's layers can degrade performance.

The Invention

UW–Madison researchers have developed a method for fabricating OPGaAs two-dimensional semiconductor-based waveguides having extremely low layer-interface roughness.

The structure is grown on a template using standard techniques and comprises a core sandwiched between upper and lower cladding layers. The layers have different, periodically arranged crystalline orientations. The surfaces between each layer undergo chemical polishing and isotropic etching that can be done *in situ*. A high-refractive-index ridge projects above the upper cladding layer and runs along the direction that light propagates. Known lithographic techniques and a combination of wet and dry etching create straight, smooth sidewalls.

Applications

- Laser projection and display
- Spectroscopy
- Optical communication
- Remote sensing
- Infrared countermeasures

Key Benefits

- Surface roughness no greater than 10 nanometers

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

- Efficient nonlinear interaction
- Low optical loss

OK



Additional Information

For More Information About the Inventors

- [Dan Botez](#)
- [Thomas Kuech](#)
- [Luke Mawst](#)

Related Intellectual Property

- [View Divisional Patent in PDF format.](#)

Tech Fields

- [Analytical Instrumentation, Methods & Materials : Lasers](#)
- [Semiconductors & Integrated Circuits : Design & fabrication](#)

For current licensing status, please contact Jeanine Burmania at jeanine@warf.org or 608-960-9846

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

OK



WARF
Wisconsin Alumni Research Foundation

| info@warf.org | 608.960.9850