



## Concentrated C5 and C6 Sugars from Biomass

[View U.S. Patent No. 9,359,650 in PDF format.](#)

**WARF: P140075US01**

Inventors: James Dumesic, David Martin Alonso, Jeremy Luterbacher

**The Wisconsin Alumni Research Foundation (WARF) is seeking commercial partners interested in developing a milder biomass pretreatment method that yields high concentrations of C5 and C6 carbohydrates and their derivatives.**

### Overview

Widespread production of sustainable fuels and chemicals will require cost-effective methods for breaking down biomass into its constituent sugars. Attaining high yields of concentrated C5 and C6 carbohydrates (e.g., xylose and glucose) is particularly challenging. Many processes have been tested but all have drawbacks such as very high temperatures or expensive acids and enzymes.

Clearly needed is a process for extracting both types of sugar under more practical reaction conditions.

### The Invention

UW–Madison researchers have developed a process for producing C5 and C6 sugars from biomass at high yields (70 to 90 percent) in a solvent mixture of water, dilute acid and GVL (gamma-valerolactone). GVL is attractive because it is effective and derived from biomass.

The biomass and solvent system may be reacted at a temperature between 50 and 250°C for less than 24 hours.

The method yields liquid and solid fractions enriched in C5 and C6 sugar, respectively. The fractions are easily separated for post-treatment upgrading. This strategy is well-suited for catalytic upgrading to furans or fermentative upgrading to ethanol at near-theoretical yield.

### Applications

- Deriving C5 and C6 sugars, furfural, levulinic acid, GVL and other chemicals from biomass

### Key Benefits

- High yield
- High concentration
- Milder reaction conditions (i.e., low acid and temperatures)
- Cleaner C6 sugars because GVL dissolves lignin
- No purification of the C5 sugar is needed because it can be upgraded to furfural in the presence of GVL.
- Cost-effective process

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

OK



**WARF**  
Wisconsin Alumni Research Foundation

| [info@warf.org](mailto:info@warf.org) | 608.960.9850

Preliminary modeling indicates the overall process is cost competitive for ethanol production, with the pretreatment being followed by enzymatic hydrolysis. Importantly, the process yields a liquid fraction containing a substantial amount (sometimes more than 95 percent) of the C5 sugars present in the raw biomass.

## Additional Information

### Related Technologies

- [WARF reference number P110124US01 describes a catalytic process for converting biomass into furan derivatives like levulinic acid and GVL.](#)
- [WARF reference number P100099US01 describes a method for producing GVL and olefins from levulinic acid.](#)

### Publications

- [Read a news story about this technology.](#)
- [Read another news story about this technology.](#)

### Tech Fields

- [Clean Technology : Biobased & renewable chemicals & fuels](#)
- [Materials & Chemicals : Biochemicals & biomaterials](#)

For current licensing status, please contact Jennifer Gottwald at [jennifer@warf.org](mailto:jennifer@warf.org) or 608-960-9854

We use cookies on this site to enhance your experience and improve our marketing efforts. By continuing to browse without changing your browser settings to block or delete cookies, you agree to the storing of cookies and related technologies on your device. [See our privacy policy.](#)

OK



**WARF**  
Wisconsin Alumni Research Foundation

| [info@warf.org](mailto:info@warf.org) | 608.960.9850