



US010182958B2

(12) **United States Patent**
Gruben et al.

(10) **Patent No.:** **US 10,182,958 B2**

(45) **Date of Patent:** **Jan. 22, 2019**

(54) **FOOTPLATE HARNESS FOR NATURAL KINEMATICS IN WALKING TRAINING APPARATUS**

(71) Applicant: **Wisconsin Alumni Research Foundation**, Madison, WI (US)

(72) Inventors: **Kreg George Gruben**, Stoughton, WI (US); **Wendy Lee Boehm**, Madison, WI (US)

(73) Assignee: **Wisconsin Alumni Research Foundation**, Madison, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 818 days.

(21) Appl. No.: **14/715,062**

(22) Filed: **May 18, 2015**

(65) **Prior Publication Data**

US 2016/0338896 A1 Nov. 24, 2016

(51) **Int. Cl.**

A61H 1/02 (2006.01)

A61H 1/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61H 1/0262** (2013.01); **A61H 1/00** (2013.01); **A61H 1/005** (2013.01); **A61H 1/0237** (2013.01); **A61H 2201/1207** (2013.01); **A61H 2201/1215** (2013.01); **A61H 2201/149** (2013.01); **A61H 2201/163** (2013.01); **A61H 2201/1621** (2013.01); **A61H 2201/1642** (2013.01); **A61H 2201/1664** (2013.01); **A61H 2201/501** (2013.01); **A61H 2201/5061** (2013.01); **A61H 2205/08** (2013.01); **A61H 2205/084** (2013.01); **A61H 2205/10** (2013.01); **A61H 2205/12** (2013.01)

(58) **Field of Classification Search**

CPC **A61H 1/0262**; **A61H 1/0266**; **A61H**

2201/149; **A61H 2205/12**; **A61H 2201/5061**; **A61H 2201/501**; **A61H 2201/1215**; **A61H 2201/1642**; **A61H 2201/163**; **A61H 2201/1621**; **A61H 2201/1664**; **A61H 1/0237**; **A61H 1/024**; **A61H 1/0244**; **A61H 2001/0248**; **A61H 2001/0251**; **A61H 1/0259**; **A61H 3/00**; **A61H 2201/0173**; **A61H 2201/0176**; **A61H 2201/018**; **A61H 2201/0184**; **A61H 2201/12**; **A61H 2201/164**; **A63B 22/007**; **A63B 22/00**

USPC **482/70-71**, **79**
See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

430,808 A * 6/1890 Naish **A63B 22/0046**
482/132
2,016,930 A * 10/1935 McCahan **A61H 1/0266**
601/27
2,109,188 A * 2/1938 Bajanova **A63B 69/0064**
182/7
3,695,255 A * 10/1972 Rodgers **A61H 1/0266**
601/31
3,774,597 A * 11/1973 Root **A61H 1/0237**
601/27

(Continued)

Primary Examiner — Rachel T Sippel

Assistant Examiner — Tu Vo



(74) *Attorney, Agent, or Firm* — Boyle Fredrickson, S.C.

(57)

ABSTRACT

A walking training device provides substantial fixation of the user's feet against a movable footplate in the direction of the user's stride while allowing toe lift and heel lift necessary for natural walking. The harness system provides an approximation of a shallow crossed four-bar linkage to provide angulation without substantial translation.

20 Claims, 5 Drawing Sheets



US 10,182,958 B2

Page 2

(56)



References Cited

U.S. PATENT DOCUMENTS

3,824,994 A * 7/1974 Soderberg, Sr. A61H 1/0259
482/51
4,614,180 A * 9/1986 Gardner A61H 9/0078
601/152
7,163,492 B1 * 1/2007 Sotiriades A61H 1/0237
482/51
8,257,284 B2 9/2012 Gruben et al.
9,248,071 B1 * 2/2016 Benda A63B 69/0057
9,713,439 B1 * 7/2017 Wu A61B 5/11
2005/0251067 A1 * 11/2005 Terry A61H 1/0214
601/5
2006/0040804 A1 * 2/2006 Barnard A63B 21/023
482/121
2006/0128537 A1 * 6/2006 Philips A61H 1/0237
482/95
2006/0229167 A1 * 10/2006 Kram A63B 21/00181
482/54
2007/0004567 A1 * 1/2007 Shetty A61H 3/008
482/69
2007/0275830 A1 * 11/2007 Lee A61B 5/1038
482/54
2009/0318267 A1 * 12/2009 Park A61H 3/00
482/8
2010/0075813 A1 * 3/2010 Ochi A61H 1/0237
482/79
2010/0248903 A1 * 9/2010 Cardile A61H 1/0262
482/51

2010/0268129 A1 * 10/2010 Park A61H 1/0237
601/35
2010/0285929 A1 * 11/2010 Bayerlein A61H 1/0237
482/54
2011/0071442 A1 * 3/2011 Park A61H 1/0262
601/35
2011/0256983 A1 * 10/2011 Malack A61H 1/0266
482/4
2012/0296242 A1 * 11/2012 Ochi A61H 1/005
601/5
2013/0053734 A1 * 2/2013 Barriskill A61N 1/36003
601/5
2014/0018216 A1 * 1/2014 Hatfield A63B 21/00185
482/131
2014/0087922 A1 * 3/2014 Bayerlein A63B 22/0235
482/54
2014/0100491 A1 * 4/2014 Hu A61H 3/008
601/27
2014/0256511 A1 * 9/2014 Smith G10H 7/00
482/8
2015/0165265 A1 * 6/2015 Tholkes A63B 22/0664
482/54
2015/0250675 A1 * 9/2015 Kalinowski A61H 3/008
482/69
2015/0257965 A1 * 9/2015 Simeone A63B 69/0064
482/146
2016/0022440 A1 * 1/2016 Ha A61F 2/68
623/24
2017/0027803 A1 * 2/2017 Agrawal A61B 5/6828

* cited by examiner






FIG. 3




FIG. 4a






FIG. 4b






FIG. 7






FIG. 8



1

FOOTPLATE HARNESS FOR NATURAL KINEMATICS IN WALKING TRAINING APPARATUS

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

--

CROSS REFERENCE TO RELATED
APPLICATION

--

BACKGROUND OF THE INVENTION

The present invention relates to a device for training human limb motion and in particular to a device that trains a walking user.

Walking impairment can be caused by disorders of the central nervous system, peripheral nervous system, and musculoskeletal system. Strokes, for example, which occur when blood flow to a region of the brain is obstructed, are a leading cause of severe long-term disability. Studies have shown that while many stroke sufferers have adequate strength at each joint, for example, for walking, the stroke may make it difficult for the sufferer to coordinate this strength for walking.

Rehabilitation efforts for stroke victims often use conventional exercise equipment to retrain correct limb motion. Such exercise equipment, for example, a stationary bicycle, provides resistance along a constrained path of movement that is intended to approximate a desired path of movement that the patient is trying to learn. This constraint may hide basic errors in muscle activation patterns and/or promote compensating behaviors by the patient without addressing the underlying muscle activation errors.

Effective training of walking can be difficult because some constraint on the motion of the patient is required to keep the patient safe, to couple the patient to the training device for measurement, and to apply training motion and forces.

SUMMARY OF THE INVENTION

The present invention provides a harness that may be used to provide mechanical coupling between a patient's feet and footplates on a training apparatus, where the footplates are supported for forward and backward motion and/or force measurement. The harness accommodates the heel lift and toe lift needed for natural walking while still closely coupling the patient's foot to the footplate with respect to motion along the stride axis. In this respect, the invention provides a balancing between foot motion guidance and foot motion freedom to permit effective training of disordered walking.

Specifically, in one embodiment, the invention provides a walking training apparatus having left and right footplates for support of a standing patient having one foot on the left footplate and one foot on the right footplate so that a front portion of each footplate is proximate to the patient's toes and a rear portion of each footplate proximate to the patient's heel. Left and right footplate support assemblies provide at least one of forward and backward motion of the left and right footplate along a stride axis of the patient and measurement of forces by the patient against the left and right footplate. A left and right harness releasably attach the

2

patient's feet to the left and right footplates, each harness providing: (a) a first flexible tension element flexibly extending between a front of the patient's foot and an attachment point at a rear of each footplate and (b) a second flexible tension element flexibly extending between a rear of the patient's foot and an attachment point at a front of each footplate.

It is thus a feature of at least one embodiment of the invention to provide a harness attachment that substantially prevents slippage between the foot and footplate while allowing heel lift, toe lift, and minor eversion, inversion, and axial rotation necessary for a normal stride.

The first flexible tension element may provide a toe pocket receiving a toe of a shoe worn by the patient, and the second flexible tension element provides a heel pocket receiving a heel of a shoe worn by the patient.

It is thus a feature of at least one embodiment of the invention to provide a harness that works with a shoe (including the patient's own shoes) to provide a simple robust attachment to the patient's feet.

The harness may further include length-adjustable connections between the first flexible tension element and second flexible tension element allowing respective pockets of the first flexible tension element and second flexible tension element to be drawn together about a patient's shoe.

It is thus a feature of at least one embodiment of the invention to provide a harness that may accommodate a variety of different patient and shoe sizes.

The length-adjustable connections may include buckles permitting separation of the first flexible tension element and second flexible tension element.

It is thus a feature of at least one embodiment of the invention to simplify attachment and detachment of the harness by allowing separation of the harness into two elements.

The first flexible tension element and second flexible tension element may be woven straps sewn to form open pouches providing the toe pocket and heel pocket.

It is thus a feature of at least one embodiment of the invention to provide a flexible harness constructed of woven straps having high tensile strength that may be securely attached to the shoe.

The first flexible tension element may provide two flexible bands extending from left and right sides of the toe pocket to a pair of attachment points at the rear of each footplate flanking at least one flexible band extending from the heel pocket to at least one attachment point at the front of each footplate.

It is thus a feature of at least one embodiment of the invention to provide additional stability to the toe of the patient's feet as they advance in the normal stride. The flanking arrangement prevents interference between the tensile elements.

The attachment point of the first flexible tension element and the second flexible tension element to the footplate may provide a releasable connection releasing under a predetermined force achievable by leg strength alone.

It is thus a feature of at least one embodiment of the invention to provide a harness that may be rapidly released from the footplate by the patient if necessary, for example, to regain balance.

The attachment points may be provided by inter-engaging hook and loop fastener material.

It is thus a feature of at least one embodiment of the invention to provide a releasable attachment mechanism that

3

is relatively resistant to shear forces generated during a normal stride but easily separated, for example, by upward lifting of the foot.

The harness may further include an electrical sensor attached to at least one of the first flexible tension element and second flexible tension element to provide an indication of a predetermined separation of at least one first flexible tension element and, second flexible tension element from its respective left or right footplate.

It is thus a feature of at least one embodiment of the invention to allow the harness to signal a stepping off of the footplate, for example, to provide an indication to a health-care professional or to affect operation of the walking apparatus.

The electrical sensor may be an electrical conductor attached to at least one of the first flexible tension element and second flexible tension element communicating with at least one releasable electrical connector to break a circuit at the predetermined separation of at least one first flexible tension element and second flexible tension element from its respective left or right footplate.

It is thus a feature of at least one embodiment of the invention to provide an electrical sensor that naturally fails in a safe mode by signaling not only when the patient's foot is removed from the footplate but also if the sensor wire or connectors are broken.

The walking training apparatus may include motors for providing forward and backward motion of the left and right footplate along the stride axis and a controller communicating with the electrical sensor and the motors to respond to the indication for stopping motion of the footplates.

It is thus a feature of at least one embodiment of the invention to allow any motorized motion of the footplates to be immediately stopped if the patient loses contact with the footplates.

The controller and the motors may provide for a periodic forward and reverse motion of the left and right footplates to mimic a natural stride in which the footplates move out of phase with respect to each other.

It is thus a feature of at least one embodiment of the invention to provide a harness particularly suitable for motor-actuated footplates that permits natural stride under such circumstances.

The footplate support assemblies may provide measurements of force applied by the footplate to the footplate support and may include an output display for displaying the measurements of force.

It is thus a feature of at least one embodiment of the invention, to provide a harness that accommodates instrumentation of leg and foot forces during contact with the footplates. This force measurement may be used to control the footplate motor actuation.

The walking training apparatus may include a framework holding the footplates and footplate supporting assemblies, the framework providing upwardly extending support structures attached to restrain lines communicating with a shoulder and hip harness receivable by the patient's shoulders and hip to provide motion restraint on a patient supported on the footplates during walking.

It is thus a feature of at least one embodiment of the invention to provide for angular stabilization for patients attempting to relearn balance during walking.

The restraints may provide a nonlinear spring-biasing force to the shoulder and hip harness.

It is thus a feature of at least one embodiment of the invention to allow the patient to explore the boundaries of their balance capabilities without risk of falling by providing

4

relatively low restoring force for low angular displacements rising quickly to a stiff restraining force for high angular displacements.

The restraints may communicate with force and angle sensors mounted to the framework to indicate forces and angles of forces applied to the harnesses by the patient during walking.

It is thus a feature of at least one embodiment of the invention to provide measurements of walking ability to provide positive feedback to the patient or analysis of the patient's walking problems for better training.

These particular objects and advantages may apply to only some embodiments falling within the claims and thus do not define the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a left-side, elevational view of a walking training apparatus of the present invention showing a patient standing on left and right footplates while walking and supported by stabilizing restraints communicating with the patient's hip and shoulder harness;

FIG. 2 is a top plan view of the walking training apparatus of FIG. 1;

FIG. 3 is a phantom view of a force-sensitive actuator to which the stabilizing restraints are attached and which may measure force magnitude and force angle on the restraints;

FIGS. 4a and 4b are fragmentary perspective views of a section of the stabilizing restraints in differing extensions demonstrating the non-linear elastic properties of the restraints;

FIG. 5 is a top plan view of one footplate of FIG. 1 showing a shoe attached by a shoe harness and safety wire to the footplate;

FIG. 6 is a perspective view of a toe portion of the harness of FIG. 5;

FIG. 7 is a perspective view of the heel portion of the harness of FIG. 5;

FIG. 8 is a simplified side view of the patient's foot during a forward leg extension of a normal stride showing a toe lift accommodated by the harness;

FIG. 9 is a figure similar to that of FIG. 8 showing a centerpoint of a nasal stride showing the foot without toe lift or heel lift; and

FIG. 10 is a figure similar to FIGS. 8 and 9 showing a rear leg extension of the normal stride and resulting heel lift accommodated by the harness.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to FIGS. 1 and 2, a walking training apparatus 10 may provide for a framework 12 providing generally a horizontal rectangular platform 14 supported against the floor. The framework 12 may provide columns 16 extending upward from the corners of the platform 14 to a point above the shoulder height of an average patient 15 standing on the platform 14.

Beneath an upper surface of the platform 14, a bearing track 18 extends generally along a stride axis 20 aligned with a stride direction of the patient 15. The stride axis 20 is generally the direction of motion of the patient's feet during walking. The bearing track 18 supports left and right carriages 22 for sliding along the bearing track 18. Each of the left and right carriages 22 provides a portion which extends upward through the upper surface of the platform 14 to attach to corresponding left and right footplates 24a and 24b.

5

The footplates **24** are generally coplanar and horizontal and may receive and support the patient's **15** feet during walking motion.

Servomotors **25** connect via belts to the carriages **22** to provide controlled motion of the footplates **24** in the direction of the stride axis **20** under the control of a computer/controller **26**. As is understood in the art, the computer/controller **26** may include a processor and computer memory, the latter of which may hold programs stored in non-transient media for implementing various operations to be described below. The computer/controller **26** may be positioned adjacent to the framework **12** and may communicate with a display **27** visible by the patient **15** walking in the walking training apparatus **10** for receiving visual guidance during walking training.

The carriages **22** will preferably include instrumentation (for example, load cells) measuring forces along each of three Cartesian axes (positive and negative forces along each axis) and torques about each of the Cartesian axes (positive and negative torques along each axis). These measurements will be communicated to the computer/controller **26** and may provide for the display of information derived from these measurements on the display **27**.

A shoulder harness **28** and hip harness **30** fit about the shoulders and hips of the patient **15**, respectively, and communicate by means of flexible restraint straps **32** with force sensitive actuators **34** attached to the columns **16** at shoulder and hip height, respectively. Thus, four restraint straps **32** separated in a horizontal plane by approximately 90 degrees communicate between the shoulder harness **28** and corresponding force-sensitive actuators **34** on each of the columns **16** and four restraint straps **32** also separated in a horizontal plane by 90 degrees, the plane being parallel to and below that of the shoulder harness **28**, and communicate between the hip harness **30** and corresponding force-sensitive actuators **34** on each of the columns **16**.

Referring now to FIG. 3, each force-sensitive actuator **34** receives a restraint cord **36** leading from the restraint straps **32** which may pass through a follower arm **38** pivotally attached to an angle resolver **40**. The angle resolver **40** pivots about a vertical pivot axis so that the angle of force exerted by the patient **15** on the restraint strap **32** within a horizontal plane may be determined and provided to the computer/controller **26**. The cord **36** may then pass through a set of centering rollers **39** and in one embodiment may be fixedly attached with respect to the columns **16** or, as shown, may be received by a spool **41** driven by a force motor/resolver **42** allowing a computer-controlled force to be applied to the cord **36** and the extension of the cord **36** to be measured. In both cases of the cord **36** being fixed or attached to the spool **41**, the force between the cord **36** and the column **16** may be measured by means of a load cell **44** communicating with the computer/controller **26**.

Referring now to FIG. 4, when the cord restraint strap **32** is fixedly attached to the columns **16**, it may include an elastic portion **46** that applies a restoring force to the patient **15** at all times when the patient is not properly vertically aligned. Restoring force is a nonlinear function of the extension of the elastic portion **46** which provides for some ability for the patient **15** to move during normal walking or experimentation with balance. Excessive leaning of the patient **15** from vertical will cause the elastic portion **46** to reach a stretch limit **48** where further extension of the elastic portion **46** is fully resisted by substantially inelastic cords of the restraint strap **32** providing an abrupt nonlinearity in the spring-biasing force and protecting the patient **15** from instability.

6

Referring now to FIG. 5, each footplate **24** may generally be movable along stride axis **20** as discussed above, for example, communicating through the surface of the platform **14** by means of slots **50** to the underlying carriages **22** which may move to provide for stride-related motion of the footplates **24**. The patient's foot (not shown in FIG. 5) may be received within a shoe **52**, for example, being a general-purpose walking or running athletic shoe roughly centered within the rectangular area of the footplate **24** and held by a harness **56** thereto. Generally the harness **56** will limit displacement of the patient's foot and shoe **52** along the stride axis **20** with respect to the center of the footplate **24**. That is, the harness **56** will prevent motion between the shoe **52** and the footplate **24** in the direction of the stride axis **20**. Nevertheless, the harness **56** will allow toe lift and heel lift (as described below), minor inversion and eversion of the foot and minor rotation about a vertical axis necessary for natural walking.

The harness **56** is attached to a safety wire **58** that electrically communicates between a releasable electrical connector **60** at a front end **62** of the footplate **24** and a releasable electrical connector **64** at a rear end **66** of the footplate **24**. Excessive motion of the harness **56** will cause one of the connectors **60** and **64** to be disconnected thereby communicating a loss of electrical continuity to an alarm detector **68**. The alarm detector **68** may communicate with the computer/controller **26** such as may be used to stop motion of the footplates **24** or provide an alarm or the like.

Referring now to FIGS. 5, 6 and 7, each harness **56** may generally include a toe portion **70** and a heel portion **72** that operate together to restrain a shoe **52** holding the foot of the patient **15**. The toe portion **70** may include a first U-shaped flexible strap **74** extending from a first attachment point **76a** at a right side of the rear end **66** of the footplate **24** and looping around the toe of the shoe **52** to a second attachment point **76b** at a left side of the rear end **66** of the footplate **24**. The strap **74** may be attached at the attachment points **76** by means of inter-engaging hook and loop fasteners, different portions situated on different ones of the strap **74** footplate **24**. These hook and loop fasteners are more resistant to shear forces (and thus help stabilize the position of the shoe **52** along the stride axis **20**) but readily disconnect under normal force by the patient **15**, for example, if the patient **15** needs to rapidly reposition his or her foot for safety.

The loop of the strap **74** proximate the toe of the shoe **52** is formed into a toe pocket **75** by means of an underlying strap **78** fitting under the toe of the shoe **52** and extending laterally to be attached at its left and right, ends to the strap **74** and an overlying strap **80** fitting over the toe of the shoe **52** also attached at its left and right ends to the strap **74**. The toe pocket **75** serves to attach the strap **74** to the toe of the shoe **52**.

An apex of the loop formed by the strap **74** may attach to left and right rearwardly extending shoe retention straps **82** terminating in adjustable buckles **84** of a type known in the art. Each of the straps **78** and **82** may also be constructed of the same material as strap **74** (for example, a nylon webbing) and assembled together by stitching.

The heel portion **72** may include a single medial flexible strap **86** extending from a third attachment point **76c** at a front end **62** of the footplate **24** centered between the left and right edges of the footplate **24**. The strap **86** may be attached at the attachment point **76c** by means of inter-engaging hook and loop fasteners, one on the end of the strap **86** and the other fixed to the footplate **24** as discussed above.

The remaining end of the medial flexible strap **86** attaches to the heel of the shoe **52** by means of a heel pocket **88**

formed by a U-shaped heel strap **90** attached at its center to an unattached end of medial strap **86** and curving about the heel of the shoe **52** and forward, to terminate at buckle portions **92** receivable by buckles **84**. The end of the strap **86** proximate to the heel attaches at its center to laterally extending strap **94** fitting beneath the heel of the shoe **52** to be attached to strap **90** at its opposite ends thereby completing the heel pocket **88**.

Each of the straps **86**, **90**, **94** may also be constructed of the same material as strap **74** and assembled together by stitching.

Adjustment of the length of the straps **82** through the buckles **84** allows the toe pocket **75** and heel pocket **88** to be drawn together about the shoe **52** to prevent substantial slippage between the shoe and the harness **54**. As so assembled, the medial flexible strap **86** is generally centered between the opposed arms of strap **74** to prevent interference between the strap **74** and **86**.

Referring now to FIG. **8**, during a normal stride by the patient **15**, when the footplate **24** is in a forward position and the patient's leg extended forwardly, the patient's heel may be against the footplate **24** and the toe elevated. At this time both strap **74** and strap **86** may be substantially without slack (in slight tension) to prevent forward or backward movement of the toe of the shoe **52** with respect to the footplate **24**. Toe and heel lifting is possible based on the geometry of the straps; however, motion in the direction of the stride axis **20** is largely resisted by the routing of the straps below the foot and the shallow angle of straps **74** and **86** and the close proximity of the attachment points **76c** and **76a** and **76b** along the stride axis **20**. Little or no strap elasticity is required. Generally the axial separation **77** of the attachment points of the straps **74** and **86** to the shoe **52** will be more than half the axial separation **79** of the attachment points of the straps **74** and **86** to the footplate **24**. Note that the strap **74** may be in part trapped beneath the heel of the shoe **52** further serving to limit axial movement of the shoe **52** with respect to the footplate **24** and to preserve tension in the straps **74** and **86**.

As the footplate **24** moves rearwardly, the shoe **52** in a normal stride will arrive to lie flat against the upper surface of the footplate **24** with neither the heel nor toe elevated as shown in FIG. **9**. In this position, minor tension on the straps **74** and **86** continues to hold the relative location of the foot with respect to the footplate **24**.

Finally, as shown in FIG. **10** when the footplate **24** is in the rearmost position, the heel of the shoe **52** may rise as is permitted by the geometry of the attachment of the straps **86** and **74** while still providing slight tension between the toe along strap **74** and the attachment point **76** and the heel along strap **86** with attachment point **76c** still preserving relative fixation of the shoe **52** with respect to the footplate **24**. In contrast to FIG. **8**, here the strap **86** may be in part trapped beneath the toe of the shoe **52** preventing slack in the straps **76** and **74** and providing improved localization of the shoe **52**.

Certain terminology is used herein for purposes of reference only, and thus is not intended to be limiting. For example, terms such as "upper", "lower", "above", and "below" refer to directions in the drawings to which reference is made. Terms such as "front", "back", "rear", "bottom" and "side", describe the orientation of portions of the component within a consistent but arbitrary frame of reference which is made clear by reference to the text and the associated drawings describing the component under discussion. Such terminology may include the words specifically mentioned above, derivatives thereof and words of

similar import. Similarly, the terms "first", "second" and other such numerical terms referring to structures do not imply a sequence or order unless clearly indicated by the context.

When introducing elements or features of the present disclosure and the exemplary embodiments, the articles "a", "an", "the" and "said" are intended to mean that there are one or more of such elements or features. The terms "comprising", "including" and "having" are intended to be inclusive and mean that there may be additional elements or features other than those specifically noted. It is further to be understood that the method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

References to "a controller" can be understood to include one or more microprocessors that can communicate in a stand-alone and/or a distributed environment(s), and can thus be configured to communicate via wired or wireless communications with other processors, where such one or more processor can be configured to operate on one or more processor-controlled devices that can be similar or different devices. Furthermore, references to memory, unless otherwise specified, can include one or more processor-readable and accessible memory elements and/or components that can be internal to the processor-controlled device, external to the processor-controlled device, and can be accessed via a wired or wireless network.

It is specifically intended that the present invention not be limited to the embodiments and illustrations contained herein and the claims should be understood to include modified forms of those embodiments including portions of the embodiments and combinations of elements of different embodiments as come within the scope of the following claims. All of the publications described herein, including patents and non-patent publications, are hereby incorporated herein by reference in their entireties.

What we claim is:

1. A walking training apparatus comprising:

- a left footplate and right footplate for support of a standing patient having one foot on the left footplate and one foot on the right footplate so that a front portion of each footplate is proximate to toes of the patient and a rear portion of each footplate proximate to a heel of the patient;
- a footplate support platform cooperating with the left footplate and right footplate to provide at least one of forward and backward motion of the left and right footplate along a stride axis of the patient, and measurement of forces by the patient against the left and right footplate; and
- a left harness and right harness releasably attaching the patient's feet to the left and right footplates, each harness providing:
 - (a) a first flexible tension element having a first end and second end, the first end of the first flexible tension element attached to a toe pocket proximate to and fixed with respect to a front of the patient's foot and the second end of the first flexible tension element attached to a rear attachment point proximate to and fixed with respect to a rear of each of the left and right footplates; wherein during operation of the walking training apparatus, the first flexible tension element and the toe pocket are configured to rotate about a horizontal axis

with respect to the rear attachment point of the left and right footplates thereby allowing toe lift; and

(b) a second flexible tension element having a first end and second end, the first end of the second flexible tension element attached to a heel pocket proximate to and fixed with respect to a rear of the patient's foot and the second end of the second flexible tension element attached to a front attachment point proximate to and fixed with respect to a point at a front of each of the left and right footplates; whereby during operation of the walking training apparatus, the second flexible tension element and the heel pocket are configured to rotate about a horizontal axis with respect to the front attachment point of each of the left and right footplates thereby allowing heel lift;

whereby the patient's feet are held against slippage with respect to a corresponding footplate along the stride axis while allowing toe lift and heel lift.

2. The walking training apparatus of claim 1, wherein the toe pocket is adapted to receive a toe of a shoe worn by the patient and the heel pocket is adapted to receive a heel of a shoe worn by the patient and wherein the first and second flexible tension elements are woven straps.

3. The walking training apparatus of claim 2, further including length-adjustable connections between the heel pocket and the toe pocket allowing the respective heel pocket and toe pocket of the first flexible tension element and second flexible tension element to be drawn together about a patient's shoe.

4. The walking training apparatus of claim 3, wherein the length-adjustable connections include buckles permitting separation of the first flexible tension element and second flexible tension element.

5. The walking training apparatus of claim 2, wherein the first flexible tension element and second flexible tension element include woven straps sewn to form open pouches providing the toe pocket and heel pocket.

6. The walking training apparatus of claim 2, wherein the first flexible tension element provides two flexible bands extending from left and right sides of the toe pocket to a pair of attachment points at the rear of each footplate flanking at least one flexible band extending from the heel pocket to at least one attachment point at the front of each footplate.

7. The walking training apparatus of claim 1, further including a shoe held by the harness and wherein the first and second flexible tension elements are substantially taut.

8. The walking training apparatus of claim 1, wherein the rear attachment point of the first flexible tension element to the footplate and the front attachment point of the second flexible tension element to the footplate each provide a releasable connection adapted to release under a predetermined force achievable by leg strength alone.

9. The walking training apparatus of claim 8, wherein the front and rear attachment points are provided by inter-engaging hook and loop fastener material.

10. The walking training apparatus of claim 1, further including an electrical sensor attached to at least one of the first flexible tension element and second flexible tension

element to provide an indication of a predetermined separation of at least one first flexible tension element and second flexible tension element from a respective one of the left or right footplates.

11. The walking training apparatus of claim 10, wherein the electrical sensor is an electrical conductor attached to at least one of the first flexible tension element and second flexible tension element communicating with at least one releasable electrical connector to break a circuit communicating with the releasable electrical connector at the predetermined separation of at least one first flexible tension element and second flexible tension element from a respective one of the left or right footplate.

12. The walking training apparatus of claim 10, further including motors for providing forward and backward motion of the left and right footplate along the stride axis and a controller communicating with the electrical sensor and the motors to respond to the indication for stopping motion of the footplates.

13. The walking training apparatus of claim 12, wherein the controller and the motors provide for a periodic forward and reverse motion of the left and right footplates to mimic a natural stride in which the footplates move out of phase with respect to each other.

14. The walking training apparatus of claim 12, wherein the footplate support platform uses the measurement of forces by the patient against the left and right footplate to control the motors.

15. The walking training apparatus of claim 1, further including an output display receiving the measurement of forces by the patient against the left and right footplate for displaying the measurement of forces by the patient against the left and right footplate.

16. The walking training apparatus of claim 15, wherein the measurements of force include force along Cartesian axes and torque about the Cartesian axes.

17. The walking training apparatus of claim 1, wherein the footplate supporting platform provides a framework providing upwardly extending support structures attached to restraint lines communicating with a shoulder and hip harness receivable by the patient's shoulders and hip to provide motion restraint on a patient supported on the footplates during walking.

18. The walking training apparatus of claim 17, wherein the restraint lines provide a nonlinear spring-biasing force to at least one shoulder and hip harness.

19. The walking training apparatus of claim 17, wherein the restraint lines communicate with force and angle sensors mounted to the framework to indicate forces and angles of forces applied to at least one harness by the patient during walking.

20. The walking training apparatus of claim 17, wherein the restraint lines communicating with the patient's shoulder are at a first horizontal plane and the restraint lines indicating with the patient's hips are in a second horizontal plane parallel to the first horizontal plane.

* * * * *