



US010391495B2

(12) **United States Patent**
Beebe et al.

(10) **Patent No.:** **US 10,391,495 B2**
(45) **Date of Patent:** **Aug. 27, 2019**

(54) **DEFORMABLE WELL AND METHOD**

4,167,955 A * 9/1979 Sharples B01L 3/0293
141/1

(71) Applicant: **Wisconsin Alumni Research
Foundation, Madison, WI (US)**

2004/0058452 A1 3/2004 Fisher et al.
2007/0017930 A1* 1/2007 Gorrie B65D 35/28
222/103

(72) Inventors: **David J. Beebe**, Monona, WI (US);
David J. Guckenberger, Jr.,
Oconomowoc, WI (US); **Hannah M.
Pezzi**, New Berlin, WI (US); **Scott M.
Berry**, Madison, WI (US)

2010/0028211 A1 2/2010 Treptow

FOREIGN PATENT DOCUMENTS

JP	2006511808	4/2006
JP	2014206396	10/2014
WO	9636436	11/1996

(73) Assignee: **Wisconsin Alumni Research
Foundation, Madison, WI (US)**

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 145 days.

Merriam-Webster definition of "cylinder".*
PCT/US2017/042987, international Search Report and Written Opin-
ion, dated Oct. 26, 2017, 16 pages.

(21) Appl. No.: **15/242,952**

* cited by examiner

(22) Filed: **Aug. 22, 2016**

(65) **Prior Publication Data**

US 2018/0050338 A1 Feb. 22, 2018

Primary Examiner — Paul S Hyun

(74) *Attorney, Agent, or Firm* — Boyle Fredrickson, S.C.

(51) **Int. Cl.**
B01L 3/00 (2006.01)

(52) **U.S. Cl.**
CPC **B01L 3/505** (2013.01); **B01L 2200/16**
(2013.01); **B01L 2300/0829** (2013.01); **B01L**
2300/123 (2013.01)

(58) **Field of Classification Search**
CPC B01L 3/505
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

2,198,256 A * 4/1940 Levy B01L 3/5021
241/DIG. 30
4,122,980 A * 10/1978 Lavery A47K 5/1214
215/253

(57) **ABSTRACT**

A deformable well structure for a microtiter plate and method are provided. The deformable well structure includes a sample container defining a well for receiving a sample therein. The sample received in the well has a concave meniscus. A deformation tool is engageable with the sample container and is moveable between a first disengaged position wherein the deformation tool is spaced from the sample container and a second, engaged position wherein the deformation tool engages and deforms at least a portion of the sample container such that the meniscus of the sample in the well is converted from concave to convex.

13 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 2A




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

DEFORMABLE WELL AND METHOD

REFERENCE TO GOVERNMENT GRANT

This invention was made with government support under CA181648 and CA014520 awarded by the National Institutes of Health and 2010-ST-061-FD0001 awarded by the DHS/ST. The government has certain rights in the invention.

FIELD OF THE INVENTION

The present invention relates generally to the preparation of samples in wells of a microtiter plate, and in particular, to a deformable well for a microtiter plate and method wherein deformation of the well converts the meniscus of a sample in the well from concave to convex.

BACKGROUND AND SUMMARY THE INVENTION

The use of a sliding lid for immobilized droplet extraction technology provides a simple approach to sample preparation. The technology contemplates a lower microtiter plate with a plurality of wells for receiving biological samples therein. An upper plate has a lower surface directed to the upper surface of the microliter plate. A force is positioned adjacent the upper plate and attracts target bound solid phase substrate in the biological sample toward the lower surface of the upper plate. The upper plate is movable from a first position wherein the target bound solid phase substrate in the biological samples are drawn to the lower surface of the upper plate and a second position wherein the target bound solid phase substrate are isolated from the biological samples.

The technology is enabled through the use of a hydrophobic lower surface of the upper plate in combination with the convex menisci of the biological samples in the plurality of wells in microtiter plate, which facilitate fluidic contact with the lower surface of the upper plate. Heretofore, to achieve the convex menisci, the wells of the microtiter plate must be accurately filled. However, such process has certain limitations. First, the stability of a convex droplet is low, as compared to a concave meniscus, making the droplets prone to spilling over the edges of the wells of the microtiter plate. The issue of spillage is exacerbated with fluids having low surface tension (e.g., lysis buffers, ethanol based solutions, detergents). As a result, the microtiter plate may be difficult to move or transport after the wells of the microtiter plates have been filled, thereby hindering the advanced preparation of plates and the disposing of plates without spillage. Second, convex droplets are difficult and/or impractical to prepackage, in part due to the aforementioned limitations. Hence, reagents must be packaged in separate containers, and thereafter, transferred to the wells of the microtiter plate. This, in turn adds steps and complexity to the process. As such, it is highly desirable to provide a mechanism which allows for the reagents/biological samples to remain concave until ready for use. Such a mechanism would enable the reagents/biological samples to be prepackaged on-chip, would simplify user protocols, and would assure that the reagents/biological samples remain in the wells of the microtiter plate so as to allow a user to manipulate the microtiter plate without the fear of spillage of the reagents/biological samples.

Therefore, it is a primary object and feature of the present invention to provide a deformable well for a microtiter plate

2

wherein deformation of the well converts the meniscus of the sample in the well from concave to convex.

It is a further object and feature of the present invention to provide a deformable well for a microtiter plate which allows for reagents/biological samples to be prepackaged therein.

It is a still further object and feature of the present invention to provide a deformable well for a microtiter plate which allows for a user to manipulate the microliter plate without the fear of spillage of the reagents/biological samples prepackaged therein.

It is a still a further object and feature of the present invention to provide a deformable well for a microtiter plate which is simple to use and inexpensive to manufacture.

In accordance with the present invention, a deformable well structure for a microtiter plate is provided. The well structure includes a sample container defining a well for receiving a sample therein. The sample received in the well, has a concave meniscus. A deformation tool is engageable with the sample container and is moveable between a first disengaged position wherein the deformation tool is spaced from the sample container and, a second engaged position wherein the deformation tool engages and deforms at least a portion of the sample container such that the meniscus of the sample in the well is converted from concave to convex.

The sample container includes a generally tubular wall having a first end defining an opening in communication with the well and a second end; and a generally flat wall closing the second end of the tubular wall. The tubular wall may be fabricated from a shape-memory polymer. It is further contemplated for the tubular wall to include a circumferentially extending bellows section formed therein. The bellows section is defined by a plurality of axially compressible pleats formed in the tubular wall.

The deformation tool may include a support bar having a recess. The recess is adapted for receiving the sample container therein. The sample container has a first cross-sectional dimension and the recess in the support bar is defined by first and second spaced sidewalls. The first and second sidewalls defining the recess in the support bar are spaced by a distance less than the cross-sectional dimension of the sample container.

In accordance with a further aspect of the present invention, a deformable well structure for a microliter plate is provided for receiving, a sample fluid therein. The deformable well structure includes a generally tubular wall having an inner surface, a first end defining an opening in communication with the well and a second end. An end wall closes the second end of the tubular wall and has an inner surface. The inner surface of the tubular wall and the inner surface of the end wall defines a well for receiving the sample fluid therein. The sample fluid received in the well has a concave meniscus. Deformation of the tubular wall converts the meniscus of the sample fluid in the well from concave to convex.

The tubular wall may be fabricated from a shape-memory polymer or include a circumferentially extending bellows section formed therein. The bellows section is defined by a plurality of axially compressible pleats formed in the tubular wall. A deformation tool may be engageable with the sample container and is configured to deform the tubular wall. The deformation tool is moveable between a first disengaged position wherein the deformation tool is spaced from the tubular wall and a second engaged position wherein the deformation tool engages and deforms the tubular wall. The deformation tool may include a support bar having first and second spaced sidewalls defining a recess therebetween. The

3

first and second spaced sidewalls are adapted to engage and to deform the tubular wall received in the recess.

In accordance with a still further aspect of the present invention, a method of converting the meniscus of a sample fluid received in a well from concave to convex is provided. The method includes the step of filling a sample container defining the well with the sample fluid. The sample container includes a generally tubular wall having a first end defining an opening in communication with the well and a second end. An end wall closes the second end of the tubular wall. The tubular wall is deformed so as to convert the meniscus of the sample fluid in the well from concave to convex.

Tubular wall may be fabricated from a shape-memory polymer. A circumferentially extending bellows section may be fabricated in the tubular wall. The bellows section is defined by a plurality of axially compressible pleats. The tubular wall may be engaged with a deformation tool. The deformation tool configured to deform the tubular wall upon contact. The deformation tool may include a support bar having first and second spaced sidewalls defining a recess therebetween. The first and second spaced sidewalls are adapted to engage and to deform the tubular wall received in the recess.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings furnished herewith illustrate a preferred construction of the present invention in which the above aspects, advantages and features are clearly disclosed as well as others which will be readily understood from the following description of the illustrated embodiments.

In the drawings:

FIG. 1 a schematic, cross-sectional view of first and second deformable wells in accordance with the present invention in a microliter plate;

FIG. 2 is a top plan view of the microliter plate of FIG. 1 and a deformation tool in a non-engaged position;

FIG. 2a is a top plan view of the microliter plate of FIG. 1 and an alternate deformation tool in a non-engaged position;

FIG. 3 is side elevational view of the microliter plate of FIG. 1 and the deformation tool of FIG. 2 in an engaged position;

FIG. 4 is a cross-sectional view of the deformation tool taken along line 4-4 of FIG. 3;

FIG. 5 is a schematic, cross-sectional view of an alternate embodiment of a deformable well in accordance with the present invention in a non-deformed configuration; and

FIG. 6 is a schematic, cross-sectional view of the deformable well of FIG. 5 in a deformed configuration.

DETAILED DESCRIPTION OF THE DRAWINGS

Referring to FIGS. 1-3, a first embodiment device of a deformable well in accordance with the present invention is generally designated by the reference numerals 10 and 10a. It is intended for a plurality of deformable wells 10 and 10a to be incorporated into microliter plate 12, as hereinafter described. Additional deformable wells may be provided in microliter plate 12 without deviating from the scope of the present invention. Further, it is noted that each deformable well 10 and 10a is identical in structure. As such, it is understood that the following description of deformable well 10 is intended to describe deformable well 10a and any other deformable well in microliter plate 12 as if fully described herein.

4

Deformable well 10 includes a generally cylindrical wall 14 having a closed lower end 16 and an open upper end 18. Preferably, cylindrical wall 14 is fabricated from a shape-memory polymer such that after deformation, cylindrical wall 14 would have the ability to return from a deformed state to its original/permanent state, as hereinafter described. However, it can be appreciated that cylindrical wall may be fabricated from other materials, such as a thin, flexible plastic, without deviating from the scope of the present invention. Cylindrical wall 14 is defined by a generally cylindrical inner surface 24 and a generally cylindrical outer surface 26 interconnected to inner surface 24 and, by upper edge 34. Upper edge 34 of cylindrical wall 14 defines opening 36 in upper end 18 thereof.

Lower end 16 of cylindrical wall 14 is closed by lower wall 20. As best seen in FIG. 3, lower wall 20 may be fabricated from a rigid material which retains its shape as cylindrical wall 14 transitions between its original state, FIG. 1, and its deformed state, FIG. 3. Alternatively, lower wall 20 may be fabricated from a shape-memory polymer such that, if deformed during deformation of cylindrical wall 14, lower wall 16 has the ability to return to its original state as cylindrical wall 14 transitions from its deformed state to its original state. Lower wall 20 is defined by a generally cylindrical inner surface 28 and a generally cylindrical outer surface 29. Inner surface 24 of cylindrical wall 14 and inner surface 28 of lower wall 20 define chamber 30 for receiving fluid 38 therein. It can be appreciated that opening 36 in upper end of cylindrical wall 14 allows for fluid communication between the interior of chamber 30 of deformable well 10 and a selected fluid transfer mechanism.

As best seen in FIGS. 1-2, adjacent deformable wells 10 and 10a are interconnected by connection sections 39 of microtiter plate 12. More specifically, connection section 39 of microtiter plate 12 extends between outer surface 26 of cylindrical wall 14 of deformable well 10 at a location spaced from open upper end 18 of cylindrical wall 14 to outer surface 26 of cylindrical wall 14 of adjacent deformable well 10a at a location spaced from open, upper end 18 of cylindrical wall 14. Connection section 39 of microliter plate 12 is generally flat and includes first and second opposite sides 42 and 44, respectively, and parallel first and second sides 46 and 48, respectively. It is contemplated for center points 45 of adjacent deformable wells 10 and 10a of microtiter plate 12 to be spaced by a distance D1, FIG. 2.

In order to deform deformable wells 10 and 10a in a predictable manner, as hereinafter described, fixture 50 is provided. Fixture 50 includes a lower support bar 52 having an upper surface 54 and a lower surface 56 interconnected by first and second, sides 58 and 60, respectively, FIGS. 3-4. Fixture 50 further includes an upper support bar 62 having an upper surface 64 and a lower surface 66 interconnected by first and second sides 68 and 70, respectively, FIGS. 2-3. Upper support bar 62 is spaced from and axially aligned with lower support bar 52. Upper surface 54 of lower support bar 52 is interconnect to lower surface 66 of upper support bar 62 by a plurality of spaced posts 72a-72c. Posts 72a and 72b define a first chamber 74 therebetween for receiving a portion of deformable well 10 with microtiter plate received within fixture 50, as herein described. Posts 72b and 72c define a second chamber 76 therebetween for receiving a portion of deformable well 10a with microtiter plate received within fixture 50, as herein described.

First side 68 of upper support bar 62 includes a plurality of spaced recesses 80 and 80a formed therein. Recesses 80 and 80a are identical in structure. As such, it is understood that the following description of recess 80 it intended to

5

describe recesses **80a** in upper support bar **62** of fixture **50** as if fully described herein. Recess **80** is defined by recessed surface **82** in first side **68**. Recessed surface **82** includes first and second generally parallel, spaced portions **84** and **86**, respectively, interconnected by a generally concave, arcuate portion **88**. The distance **D2** between first and second portions **84** and **86**, respectively, of recessed surface **82** of each recess **80** and **80a** is less than the diameters **D3** of deformable wells **10** and **10a**, for reasons hereinafter described. It is further contemplated for adjacent recesses **80** and **80a** to be spaced from each other such that the midpoint **81** between first and second generally parallel, spaced portions **84** and **86**, respectively, of recess **80** is spaced from the midpoint **83** between first and second generally parallel, spaced portions **84** and **86**, respectively, of adjacent recess **80a** by a distance generally equal to the distance **D1** between center points **45** of adjacent deformable wells **10** and **10a** of microtiter plate **12** to facilitate alignment of deformable wells **10** and **10a** of microtiter plate **12** with corresponding recesses **80** and **80a**, respectively, in fixture **50**.

In operation, chambers **30** in deformable wells **10** and **10a** of microtiter plate **12** are filled with fluid **38**. As best seen in FIG. 1, fluid **38** in deformable wells **10** and **10a** of microtiter plate **12** have generally concave menisci **90**. In order to reverse the shapes of concave menisci **90** of fluid **38** in deformable wells **10** and **10a** to be convex, microtiter plate **12** aligned with fixture **50** such that each deformable wells **10** and **10a** is aligned with a corresponding recess **80** and **80a**, respectively, in fixture **50**. Thereafter, microtiter plate **12** is inserted into fixture **50** such that each deformable well **10** received between first and second, portions **84** and **86**, respectively, of recessed surface **82** of recess **80** and such that upper support bar **62** is located between connection sections **39** of microtiter plate **12** and lower support bar **52**. Similarly, deformable well **10a** is received between first and second portions **84** and **86**, respectively, of recessed surface **82** of recess **80a** such that upper support bar **62** is located between connection sections **39** of microtiter plate **12** and lower support bar **52**. As deformable wells **10** and **10a** are inserted into corresponding recesses **80** and **80a**, respectively, in fixture **50**, cylindrical wall **14** of deformable well **10** and cylindrical wall **14** of deformable well **10a** are deformed such that the volumes of deformable wells **10** and **10a** are reduced in a predictable manner. Reducing the volumes of deformable wells **10** and **10a** causes a reversal in the shape of the menisci **90** of fluid **38** such that menisci **90** become convex, FIG. 3.

Alternatively, referring to FIG. 2a, it is contemplated for recessed surface **82** in first side **68** of upper support bar **62** to be defined by first and second diverging portions **84a** and **86a**, respectively, extending from a common vertex **88a**. The distance **D4** between terminal ends **85** and **87** of first and second diverging portions **84a** and **86a**, respectively, of recessed surface **82** of each recess **80** and **80a** is greater than the diameters **D3** of deformable wells **10** and **10a**. In addition, it is further contemplated for adjacent recesses **80** and **80a** to be spaced from each other such that the midpoint **89** between terminal ends **85** and **87** of first and second diverging portions **84a** and **86a**, respectively, of recess **80** is spaced from the midpoint **91** between terminal ends **85** and **87** of first and second diverging portions **84a** and **86a**, respectively, of adjacent recess **80a** by a distance generally equal to the distance **D1** between center points **45** of adjacent deformable wells **10** and **10a** of microtiter plate **12** to facilitate alignment of deformable wells **10** and **10a** of microtiter plate **12** with corresponding recesses **80** and **80a**, respectively, in fixture **50**.

6

In operation, as microtiter plate **12** is inserted into fixture **50**, each deformable well **10** is received between first and second portions **84a** and **86a**, respectively, of recessed surface **82** of recess **80** and deformable well **10a** is received between first and second portions **84a** and **86a**, respectively, of recessed surface **82** of recess **80a**. As deformable wells **10** and **10a** are inserted into corresponding recesses **80** and **80a**, respectively, in fixture **50**, cylindrical wall **14** of deformable well **10** and cylindrical wall **14** of deformable well **10a** are deformed such that the volumes of deformable wells **10** and **10a** are reduced in a predictable manner. It can be appreciated that as deformable wells **10** and **10a** are inserted further into corresponding recesses **80** and **80a**, respectively, toward vertices **88a**, cylindrical wall **14** of deformable well **10** and cylindrical wall **14** of deformable well **10a** are further deformed thereby gradually reducing the volumes of deformable wells **10** and **10a**. Hence, it can be understood that the further insertion of deformable wells **10** and **10a** into corresponding recesses **80** and **80a**, respectively, will not only cause a reversal in the shape of the menisci **90** of fluid **38** such that menisci **90** become convex, but allow for a user to control the height of the convex, menisci **90** of fluid **38** and the volume of fluid **38** within deformable wells **10** and **10a**.

Referring to FIGS. 5-6, a second embodiment device of a deformable well for microtiter plate **12** is generally designated by the reference numeral **100**. It is intended for a plurality of deformable wells **100** to be incorporated into microtiter plate **12** without deviating from the scope of the present invention. Deformable well **100** includes a generally cylindrical wall **104** having a closed lower end **106** and an open upper end **108**. It is contemplated to fabricate cylindrical wall **104** from a shape-memory polymer such that upon deformation, cylindrical wall **104** has the ability to return from a deformed state to its original/permanent state, as hereinafter described. However, it can be appreciated that cylindrical wall may be fabricated from other materials, such as a thin, flexible plastic, without deviating from the scope of the present invention. Cylindrical wall **104** is defined by a generally cylindrical inner surface **110** and a generally cylindrical outer surface **112** interconnected to inner surface **110** by upper edge **114**. Upper edge **114** of cylindrical wall **104** defines opening **116** in upper end **108** thereof.

Lower end **106** of cylindrical wall **104** is closed by lower wall **120** fabricated from a rigid material which retains its shape as cylindrical wall **104** transitions between its original state and its deformed state. Lower wall **120** is defined by a generally cylindrical inner surface **122** and a generally cylindrical outer surface **124**. Inner surface **110** of cylindrical wall **104** and inner surface **122** of lower wall **120** define chamber **126** for receiving fluid **38** therein. It can be appreciated that opening **116** in upper end **108** of cylindrical wall **104** allows for fluid communication between the interior of chamber **126** of deformable well **100** and a selected fluid transfer mechanism.

To facilitate deformation of deformable well **100** in a predictable manner, cylindrical wall **104** may include a circumferentially extending bellows section **130**. More specifically, bellows section **130** includes axially compressible pleats **132** formed therein. In operation, chamber **126** of deformable well **100** of microtiter plate **12** is filled with fluid **38**. As best seen in FIG. 5, fluid **38** in deformable well **100** of microtiter plate **12** has a generally concave meniscus **90**. In order to reverse the shape of concave meniscus **90** of fluid **38** in deformable well **100** to be convex, a generally flat surface **134** such as fixture, table top or user's hand is positioned against outer surface **124** of lower wall **106** of

7

deformable well **100**. Thereafter, flat surface **134** is urged axially against lower wall **120** such that pleats **132** of bellows section **130** of cylindrical wall **104** collapse in a predictable manner for a desired axial distance. As cylindrical wall **104** of deformable well **100** collapses, the volume of chamber **126** of deformable well **100** is reduced. This reduction in volume of chamber **126** of deformable well **100** causes a reversal in the shape of meniscus **90** of fluid **38** such that meniscus **90** is convex.

It can be appreciated that the above descriptions of devices are merely exemplary of the present invention. Various modes of carrying out the invention are contemplated as being within the scope of the following claims particularly pointing out and distinctly claiming the subject matter, which is regarded as the invention.

We claim:

1. A deformable well structure for a microtiter plate, comprising:

a sample container including a generally cylindrical wall at least partially defining a well for receiving a sample therein; and

a deformation tool including a fixture having:

a support bar; and

a recessed surface in the support bar defining a recess and being engageable with the wall of the sample container, the recessed surface having a position fixed relative to the support bar;

wherein:

one of the sample container and the fixture being moveable between a first disengaged position wherein the sample container is spaced from the recessed surface in the support bar and a second engaged position wherein the sample container is received in the recess in the support bar and engages the recessed surface in the support bar;

the recessed surface defining the recess in the support bar deforms at least a portion of the sample container with the sample container received in the recess such that the meniscus of the sample in the well is convex;

the sample container has a first cross-sectional dimension greater than a cross-sectional dimension of the recess in the first disengaged position and in the second engaged position such that the recessed surface deforms the sample container as the sample container and the fixture are relatively moved from the first disengaged position to the second engaged position.

2. The deformable well structure of claim 1 wherein the cylindrical wall of the sample container includes a first end defining an opening in communication with the well and a second end and wherein the sample container further includes a generally flat wall closing the second end of the cylindrical wall of the sample container.

3. The deformable well structure of claim 2 wherein the cylindrical wall is fabricated from a shape-memory polymer.

4. The deformable well structure of claim 1 wherein the recessed surface in the support bar is defined by first and second spaced sidewalls, the first and second sidewalls defining the recess in the support bar being spaced by a distance less than the cross-sectional dimension of the sample container.

5. The deformable well structure of claim 1 wherein the one of the sample container and the fixture of the deformation tool is moveable between the second engaged position and a third engaged position, wherein the convex meniscus of sample fluid has a first height with the one of the sample container and the fixture of the deformation tool in the

8

second engaged position and a second height with the deformation tool in the third engaged position.

6. A deformable well structure for a microtiter plate for receiving a sample fluid therein, comprising:

a generally tubular wall having an inner surface, a first end defining an opening and a second end;

an end wall closing the second end of the tubular wall and having an inner surface, the inner surface of the tubular wall and the inner surface defining a well for receiving the sample fluid therein; and

a volume reduction arrangement configured to selectively alter a configuration of the tubular wall, the volume reduction arrangement including a fixture having:

a support bar; and

a recessed surface in the support bar defining a recess and being engageable with the tubular wall, the recessed surface having a position fixed relative to the support bar;

wherein:

one of the tubular wall and the fixture being moveable between a first disengaged position wherein the tubular wall is spaced from the recessed surface of the support bar and a second engaged position wherein at least a portion of the tubular wall is received in the recess in the support bar and engages the recessed surface of the support bar;

the sample fluid has a meniscus;

movement of the one of the tubular wall and the fixture of the volume reduction arrangement to the second engagement position results in the meniscus of the sample fluid projecting from the opening in the tubular wall and being convex; and

the tubular wall has a first cross-sectional dimension greater than a cross-sectional dimension of the recess in the first disengaged position and in the second engaged position such that the recessed surface deforms the tubular wall as the tubular wall and the fixture are relatively moved from the first disengaged position to the second engaged position.

7. The deformable well structure of claim 6 wherein the deformation of the tubular wall reduces the volume of the well.

8. The deformable well structure of claim 6 wherein the tubular wall is fabricated from a shape-memory polymer.

9. The deformable well structure of claim 6 wherein the recessed surface of the fixture includes first and second spaced sidewalls defining the recess therebetween, the first and second spaced sidewalls adapted to engage and to deform the tubular wall received in the recess.

10. A deformable well structure for a microtiter plate for receiving a sample fluid therein, comprising:

a generally tubular wall having an inner surface, a first end defining an opening and a second end;

an end wall closing the second end of the tubular wall and having an inner surface, the inner surface of the tubular wall and the inner surface defining a well for receiving the sample fluid therein; and

a volume reduction arrangement configured to selectively alter a configuration of the tubular wall, the volume reduction arrangement including a fixture having a recessed surface defining a recess in the fixture;

wherein:

one of the tubular wall and the fixture being moveable between a first disengaged position wherein the tubular wall is spaced from the recessed surface of the fixture and a second engaged position wherein at least a

9

portion of the tubular wall is received in the recess in the fixture and engages the recessed surface of the fixture;

the sample fluid has a meniscus;

movement of the one of the tubular wall and the fixture of the volume reduction arrangement to the second engagement position results in the meniscus of the sample fluid projecting from the opening in the tubular wall and being convex; and

the end wall is rigid and closes off the second end of the tubular wall.

11. A method of forming a convex meniscus of a sample fluid received in a well, comprising the steps of:

filling a sample container defining the well with the sample fluid, the sample container including:

a generally tubular wall having a first end defining an opening in communication with the well and a second end; and

an end wall closing the second end of the tubular wall;

providing a fixture having:

a support bar; and

a recessed surface in the support bar defining a recess, the recessed surface having a position fixed relative to the support bar; and

moving one of the sample container and the fixture between a first disengaged position wherein the sample

10

container is spaced from the recessed surface of the support bar and a second engaged position wherein the sample container is received in the recess in the support bar such that the tubular wall engages the recessed surface in the support bar and deforms;

wherein:

deformation of the tubular wall causes the sample fluid to form a convex meniscus; and

the sample container has a first cross-sectional dimension greater than a cross-sectional dimension of the recess in the first disengaged position and in the second engaged position such that the recessed surface deforms the sample container as the sample container and the fixture are relatively moved from the first disengaged position to the second engaged position.

12. The method of claim **11** comprising the additional step of fabricating the tubular wall from a shape-memory polymer.

13. The method of claim **11** wherein the recessed surface includes first and second spaced sidewalls defining the recess therebetween, the first and second spaced sidewalls adapted to engage and to deform the tubular wall received in the recess.

* * * * *